

References

- Anthony, M.C., Madan, B. and Dennis, W.S., Jr. (October 2007) Proceedings of International Rubber Conference, Cleveland, Ohio
- Arroyo, M., Manchado, M. A. L., Valentin, J. L., Carretero, J. (2006/11/14) Morphology/Behavior relationship of nanocomposites based on natural rubber/epoxidized natural rubber blends, *Science and Technology*, 67
- Aoshuang, Y., Zheugtao, G. , Li Li., Ying, Z., Peng, Z. (2002) The mechanical properties of radiation-vulcanized NR/BR blending systems, *Radiation Physics & chemistry* 63, pp.497-500
- Blow, C. M. (1971) *Rubber Technology and Manufacture*, Butter worth and co. ltd, Londen
- Bueche, F. (1962) *Physical Properties of Polymers*, John Wiley & Sons, New York
- Coran, A. Y. (June 1-5 1987) Blends of Dissimilar Rubbers cure rate incompatibility, *Chemistry and Technology*, Vol.61, International rubber conference, Harrogate, UK
- Coddington, D.M. (1973) Halogenated butyl tubeless tire inner liner background, US patent 3769122
- Colin, Evans W. (1981) *Practical Rubber Compound and Processing*, Applied Science Publishers Ltd, Londen and New Jersey, USA, Chapter 4
- Costa, H. M. De., Nunes, R. C. R., Visconte, L. I. Y., Furtado, C. R. G. (Rio De Janeiro, BR (Nov. 05 2001) Physical properties and swelling of natural rubber compounds containing rice husk ash, *Raw rubber and applications*
- Corish, P. J. (Sep. 14-16 1966) Fundamental studies of rubber blends, Dunlop Research Centre, Donlop Rubber Co. Ltd, Birmiugham, England, Presented at a meeting of the division rubber chemistry, American society, New York, pp. 324-341
- Data, R. N.(2001) Rubber curing systems, *RAPRA Review Reports* , Vol. 1, P. 31
- Dogadkin, B., Kukin. B., Trazova, Z., Skerodumova, Z., Tutorskii, Kolloidn, I., and Zh.(1956) Vol.18, p.413
- Dick, J.S., Melsom, J .A. (Aug. 2003) *Basic Rubber Testing*, chapter- 5, 6, 7, pp. 90 -111, Bridgeport, NJ

Edirisinghe, D. G., Seneviratne, D., Siriwardana, T. A. A. I. and Dharmadas, A. D. J. D. (2010) Mechanical and Dynamic mechanical Property Evaluation of NR/ SBR / BR Composites based on a tyre tread formulation, *Rubber compounding Asia*, paper. 17, pp. 186-201

Elliott, D.F. (1986) *NR Technology*, No.1, 17

Franta, I. (1989) *Elastomers & Rubber Compounding Materials*, Chapter 6

Fusco J. V and Hous, P. in *Rubber Technology*, (1987), 3rd Ed, Morton M Ed, Van Nostrand Reinhold, New York, pp. 288-362

Halobutyl tire inner liners/Thermax® Medium Thermal Black N990 Blended with N660 in halobutyl inner liners, Cancarb, 1702 Brier Park cres. N. W. Medicine hat, A,B,Canada TICIT8

Hindawi, A., Higgins, J. S. and Weiss, R. A.(3-5 April 1991) Flow-induced mixing and demixing in polymer blends, *Polymer Physics*, Bristol, UK

Hadi, A.H. and Botka, D.L. (2007) Characterizing the effect of ultra fine scrap tire rubber on tire compound properties paper presented at a meeting of the Rubber Division , ACS, 17-18 October, Cleveland, OH, Paper # 97

Ismail, H., Hairunizam, H. M.(2001) The effect of a compatibilizer on curing characteristics, mechanical properties and oil resistances of styrene butadiene rubber/epoxidized natural rubber blend, *European Polymer Journal* 37, pp.39-47

Koczerowska, E., Jurkowska, B., Jurkowski, B. B.(1988) Studies of Sulfer Behavior in Rubber Compounds, *Journal of Applied Polymer Science*, Vol. 69, pp.1531-1536

Karus, G. (1965) *Rubber Chem. Technol.* , 38 ,1070

Lai, J. Y., Yamada, S., Kamide, K. and Manbe, S. I., Kawai, T. (1986) Gas permeability of composite membranes, *Journal of Applied Polymer Science*, Vol. 32, pp.4625-4637

Lee, B. L. and Singleton, C. J. J. (1979) *Appl. Polym. Sci.*24, 2169

Liyanage, S., Thilakaratna, L. M. K., Nethsinghe, L. , Siriwardana, S., Mendis, L. P, Fernando, N., Karunanayeke, L. and Chandrarathne, T. L. (1987) *Polymer Industry of Sri Lanka*, Liyanage, S. (editor), *Institute of Chemistry Ceylon* pp.104-135

Mohammed, S. A. H., Timer, J., Walker, J. (1981) Utility of electron beam irradiation for halobutyl inner liners, *Radict . Phys. Chem.* Vol. 18 No. 3-4, pp. 433-444

Martin, J. M., Smith, W. K. (2004) *Hand of Rubber Technology, Compounding, Manufacturing and Uses of Rubber, 1st Edition*, CBS publishers and distributors, Newdili, Bangalow, chapter. Vol.1, Chapter-2

Mohammed, S. A. H., Timer, J. Wallaer, J. (1981) Utility of electron beam irradiation for halobutyl inner liners". *Radiat. Phys. Chem.* Vol. 18 No.3-4, pp.433-444

Ministry of Plantation Industries, Rubber Sector, (Chapter3), *Statistical Information on Plantation Crops-2010, Plantation Sector Statistical Pocket Book -2010*, Colombo: State Printing Corporation, 2011

NHTSA Tire Aging Test ,Development Project-Tire inner liner Analysis, US Department of Transportation, National Highway Traffic Safety Administration, www.uhtsa.gov, March 2010

Rattanasom, N., Poonsuk, A., Makmoon, T .,(2005) Effect of curing system on the mechanical properties and heat ageing resistance of NR/Tire tread reclaimed rubber blend, *Polymer Testing*, 24, pp. 728-732

Patlazhan, S. , Schlatter, G., Serra, C., Bouqney, M., Muller, R., (2006) Shear-induced fractal morphology of immiscible reactive polymer blends , *Polymer* 47, pp.6099-6106

Robert, F. Ohm. (1990) *The Vanderbilt rubber hand book*, R.T. Vanderbilt Company Inc. 13th Edition, Chapter 2, 3, 4



University of Moratuwa, Sri Lanka
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

Roland, C. M. (October 6-7 1987) Interactions in a miscible polymer blend, *American chemical society*, Cleveland, Ohic.

Rehner, J., Jr. and Peter, E. Wei., (Nov. 1967) Heterogeneity and Crosslinking of elastomer blends Investigation of chlorobutyl with highly unsaturated elastomers, Esso Research and Engineering Company, Linden. New Jersey, Proceeding of the D K G.

Rodgers, B., Webb, R. N. and Weng, W. (June 2006) Advance in tire inner liner technologies, *Rubber World*

Silva, K. G. K. De., (1992) *RRISL*, Rathmalana, Improving Morphology and properties of NR/NBR blends with NR/PMMA graft Co polymers

Steven, Blow.(1998) *Handbook of Rubber Technology, 9th Edition*, Chapter -28

Turturro, A., Flqui, L., Lopvevite, M., Ginliani, G., Mowdood, S. and Serria, A. ,

Genova and Milano (Italy), (2001) Tubeless tyre inner liner morphology & physical properties of elastomers blend. , *Elastomer and plastics*. Vol. 1, No. 2, pp.36-42
Tenbrinke, J.W.(1st quarter 2003) Rubber Technology Group, University of Twente, Coupling agents in Silica filled tyre rubbers, *Natuurrubber / Natural Rubber* 29

Thomas, L., Jablonowiki and Jalin, M. Mitchell Uniroyal Chemical Co., Inc. Nangatuck, Connecticut, USA and Dr. B. Suryauarayanan Herdillia (1990) Chemicals Limited., Bombay, India, The use of EPDM in butyl inner tubes for improved performance

Waddell, W. H., Napier, B., Rouckhout, DR., (2010) Polymer for inner liner applications-new developments, Raw material and applications, pp. 483-488

Warley, R. L., Halladay, J. R.(11th June 2005) Effect of ambient temperature and cure state on the age stiffening of a cured NR/BR blend, *Polymer Testing* 24 , pp.678-683

Walters, M. H., and Keyte, D. N. (1965) *Rubber Chem. Technol.*, 38, 62

Yasuhisa, M. (Sumitomo Rubber Ind. Ltd., Kobe), Akihiro, N. (Sumitomo Rubber Ind.Ltd., Kobe), Takashi, I. (Tokyo Inst. Technol., Tokyo),(2000) Dynamic vulcanization of halogenated butyl rubber/natural rubber blend, *Journal of the society of Rubber Industry, Japan* (G0157A),Vol.73, No.1, pp.62-69

Zhang, S., Ge, S., Trang, B., Koga , Rafailovich, M. H., Sokolar, J. C., Peiffe, D .G., Li, Z., Dais, K., McElrath, K. O., Lin, M. Y., Satija, S. K. , Urquhart, S .G., Ade, H. & Nguyen, D.(2001) Effect of carbon black and silica fillers in elastomer blends, *Macromolecules, American Chemical Society* Vol.34, pp. 7056-7065