

LB/DON/99/03

CE 01/468

STUDY OF STORM WATER DRAINAGE SYSTEM ACROSS ROADS
CASE STUDY ON COLOMBO – HORANA ROAD
(Section between Kohuwala and Piliyanthala Intersections)

A DESERTATION SUBMITTED IN PARTIAL FULFILMENT FOR THE DEGREE
OF MASTER OF ENGINEERING

BY

A. M. Mansoor
C.Eng., MIE(SL), MIHT(UK.)

UNIVERSITY OF MORATUWA, SRI LANKA
MORATUWA

624 "03"
625-735 (949-1)



University of Moratuwa, Sri Lanka
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

SUPERVISED BY

Dr. Ashok Peiris.
&
Dr. N. T. S. Wijeyasekera.

University of Moratuwa



79221

DEPARTMENT OF CIVIL ENGINEERING
UNIVERSITY OF MORATUWA
SRI LANKA.

79221

FEBRUARY, 2003

79221



ACKNOWLEDGEMENT

I take this opportunity to express my sincere gratitude and appreciation to Dr. Ashok Peiris for his guidance, encouragement and valuable advice given through out this study. And also my special appreciation to Dr. N.T.S. Wijsekera for his initial guidance, encouragement and valuable advice extended as and when sought by me for this study.

I also would like to express my special thanks to Mr. M.G. E. Perera, Director Highway designs, Mrs. R A S K Kaluarachchi, Deputy Director Highway Designs and other staff members of the Road Development Authority and the staff of the Highway and Traffic Engineering section of the Civil Engineering Department of the University of Moratuwa for their kind cooperation provided during the period of study.

The assistance rendered by Engineers of the Pacific Consultant International, the Irrigation Department officials, the staff of the Meteorological Department, in the process of data collection for this study is invaluable.

I fondly remember my diseased father, my loving mother, loving wife, my family members, and the family members of my wife for their continuous moral and emotional support with encouragements extended to my studies and to my life.

ABSTRACT.

The Government of Sri Lanka has planned to develop its southern part in many areas to boost the socio and economic activities. Among the planned development activities, the infrastructure development takes the priority, particularly the improvements to existing roads and new road constructions. The proposed southern highway construction is one such major project that is currently being undertaken. And there are many link roads also to be developed to connect with the proposed highway, the Colombo – Horana road is one of the main link road to be connected to the proposed Southern Highway at Kahatotuwa.

At present, many sections of the Colombo – Horana road are in a deplorable conditions and inundate very often when it rains, mainly due to inadequate drainage facilities or inadequate road elevation. The road section, between Kohuwala and Piliyanthala intersections which is approximately 7km in length, and there are about twenty five (25) culverts in the section, is also has the very same problem mentioned above. Therefore, this report deals in Identifying the existing drainage problems of the section, Checking the adequacy of all the existing drainage structures within the study area and proposing a suitable design methodology for Road Trace, Safe Road Elevation corresponding flood to the required Return Period and for designing the drainage structure openings. And also to see the possibility of analyzing the drainage problem in using Geographical Information System (GIS).

CONTENTS

	Page No.
*ABSTRACT	
* ACKNOWLEDGEMENT	
1. INTRODUCTION	1
1.1 General	1
1.2 The Description of the Project.	2
1.3 Title of the Research.	5
1.4 Research Outline and Objectives of the Project.	5
1.5 Methodology to be Adopted.	5
1.6 Expected Results of the Project.	5
1.7 Mechanism of Damage to Highway.	6
1.8 Main Types of Drainage.	7
1.9 Principle of Good Drainage.	11
1.10 Provision of Adequate Drainage.	12
1.11 Source of Surface Water.	12
2. LITERATURE REVIEW	13
2.1 Intensity of Rainfall.	13
2.2 Runoff Coefficient.	16
2.2.1 The Factors Affecting the Relation to Peak Runoff to Rainfall.	19
2.2.2 Design Values of C for Small Rural Catchments.	28
2.3 Time of Concentration.	30
2.4 Intensity – Duration – Frequency Curves.	33
2.5 Determination of Peak Flow Discharge.	36
2.5.1 General.	
2.5.2 Some Empirical Rational formula in Use	36
2.5.3 Limitations of the Rational Method.	48
3. OSERVATIONS AND RESULTS.	53
3.1 Site Inspection and Data collection.	53
3.2 Maps and Data Collected.	54
3.3 Identifying the existing problem	55
3.4 Details of Existing Culvert.	57
3.5 Checking the Existing Slope.	58
3.6 Specimen Calculation for Time of Concentration.	59
3.7 Verifying results obtained by <i>Culvert Master</i> Software.	67
3.8 Design Flow Chart.	71
3.8.1 Specimen Runoff Calculation.	72
4. SELECTING A TRACE.	76
4.1 General	76
4.2 Objectives of Route Location.	77
4.3 Process of Selecting a route.	77
4.4 Factors to be Considered in Selecting a Route	78

4.5	Information Gathering.	78
4.6	Development of Alternative Routes and Final Selection.	83
5.	ELEVATION.	88
6.	PROPOSING A DESIGN METHODOLOGY.	91
6.1	Selection of Trace.	91
6.2	Selection of Road Elevation.	92
6.3	Design Flow of Culvert.	98
6.4	Factors Affecting Selection of Water Way Structures.	99
6.5	Culvert Design.	102
6.5.1	Introduction.	102
6.5.2	Field Survey.	102
6.5.3	Culvert Hydraulics.	103
6.5.4	Velocity of Culvert.	113
6.5.5	Culvert Design Procedure.	114
6.5.6	Computer Modeling.	120
7.	USE OF GEOGRAPHIC INFORMATION SYSTEM IN STORM WATERDESIGN.	121
7.1	Introduction.	121
7.2	Some Related Previous Studies.	126
8.	DISCUSSION.	128
8.1	Selection of Appropriate Structure.	128
8.2	Selecting a Trace.	129
8.3	Selection of Road Elevation.	129
8.4	General Aspects.	130
9.	CONCLUSION.	131
10.	REFERENCES.	133
11.	LIST OF TABLES.	
2.1	Recommended Average Recurrence Interval for Design.	14
2.2	Return Period and Average Exceedance Probability of Design Flood.	14
2.3	Typical Values for Runoff Coefficient C in Urban Areas.	29
2.4	Equations for Intensity – Duration – Frequencies.	35
3.4	Details of Existing Culverts.	57
3.5	Checking Existing Slopes.	58
3.6	Time of Concentration.	61
3.7	Extrapolation of Intensity values for Return Period of one Year.	62
3.8	Intensity for Return Period for One Years.	64
3.9	Intensity for Return Period 25 Years.	66
3.8.2	Adequacy Check, When R = 1 year flood.	74
3.8.3	Adequacy Check, When R = 25 years flood.	75



5.1	Recommended Gradients for different Terrain types.	89
5.2	Minimum Gradient for Drainage Purpose.	90
12.	LIST OF FIGURES.	
1.0	Drainage Canal Net work of Greater Colombo Area.	04
2.1	Base Flow Diagram.	17
2.1.1	Runoff Coefficient for Urban Catchment.	21
2.2	Rational Method Theory and Actual Hydrograph.	23
2.3	Infiltration Losses and Runoff during a Storm, and the initial loss.	24
2.4	Effects of Wet and Dry antecedent Conditions on Storm losses & Runoff	25
2.5	Standard IDF Curves of a Basin.	33
2.6	Comparison of Flows by Actual and Rational Methods.	50
2.7	Relationship Between Flow Elements.	52
3.1	Catchment Area for Culvert at Chainage 3+172.	60
3.2	IDF Curve for R=1 Year.	63
3.3	IDF Curve for R=25 Years.	65
3.4	Design Flow Chart.	71
4.1	Alternative Routes.	86
13.	ANNEXURES.	133

