REFERENCES

R.Aaobe, "Plastic foam in Road Embankments," Ground Engineering, Vol 19 No 1, and pp 30-31, 1986.

T.M.Allen and A.P.Killan, "Use of wood fibre and geotextile reinforcement to build an embankment across soft ground," Transportation research board, 72nd annual meeting, Washingston, DC, 10-14 January 1993.

A.Asaoka, M.Nakano and M.Matsuo, "Prediction of the partially drained behaviour of soft clays under embankment loading. Soils and foundation, Vol 32: pp 41-58,1992.

M.S.S.Almeida, A.M.Britto and R.H.G.Parry "Numerical modeling of a centrifuged embankment on soft clay" *Canadian Geotechnical Journal*, Vol 23, pp103-114,1986.

J.R.Beatty, "Physical Properties of Rubber Compounds", *Mechanics of Pneumatic Tires*, S.K.Clark, ed., United States Department of Transportation, National Highway Traffic Administration, Washington, D.C., 1981.

A.Bernal, C.W. Lovell and R. Salgado "Laboratory Study on the Use of Tire Shreds and Rubber-Sand in Backfills and Reinforced Soil Applications." FHWA/IN/JHRP-96/12, Purdue University, West Lafayette. Indiana, 1996.

T.Bressette, "Used tire material as an alternative permeable aggregate," Report No.FHWA/CA/TL-84/07,Office of transportation laboratory, California, 1984.

P.J. Bosscher, T.B. Edil, and N.N. Eldin, "Construction and Performance of a Shredded Waste Tire Test Embankment", *Transp. Res. Rec. No* .1345, 44-52, Transportation Research Board, Washington, D.C., 1992.

P.J.Bosscher, T.B.Edil, and S.Kuraoka, "Design of Highway Embankments Using Tire Chips", J.Geot.Geoenv.Eng., Vol. 123, No. 4, 295-304, 1997.

A.M.Britto, & M.J.Gunn, "Critical state soil mechanics via finite elements" Chichester: Ellis Horwood, 1987.

R.G.Brown, "Repairing Road Embankments in Mountainous Terrain with Polystyrene" 3rd International Conference on Slope Stability and Safety of Infrastructure in Singapore, 2002.

W.Clarken "Expanded Polystyrene for Road Construction – Proceedings of Seminar on Lighweight Fill in road construction, National Institute for physical planning and Construction research, Dublin, 1986.

C.R.I.Clayton, M.C.Matthews, & N.E.Simons, Site investigation. Blackwell Sciences Ltd, 1995.

L.de Boer, "Expanded polystyrene in highway embankments," Geotechnical news, p25, March 1988.

T.A.Downs, D.N.Humphery, L.E.Katz & C.A.Rock, "Water quality effects of using tire chips below the ground water table." Augusta, Maine Department of Transportation, USA.

T.B.Edil, and P.J.Bosscher, "Engineering properties of tyre chips and soil mixtures." Geotech testing journal, ASTM, 17(4), 453-464,1994.

T.B.Edil and P.J.Bosscher, "Development of Engineering Criteria for Shredded WasteTires in Highway Applications", Research Report GT-92-9, Wisconsin Department of Transportation, Madison, WI, September 1992.

K.Flaate, "The (Geo) Technique of super light materials," The art and science of Geotechnical engineering: The art and science of geotechnical engineering: At the dawn of the twenty first century, A volume honoring B.Ralph, Prentice hall, Englewood cliffs, NJ, pp.19-205, 1989.

G.J.Foose, C.H.Benson, and P.J.Bosscher, "Sand reinforced with shredded waste tires, "Journal of Geotechnical Engineering, Vol.122, No.9, pp.760-767, 1996.

G.Hunter and R. Fell "Prediction of impending failure of embankments on soft ground" *Canadian Geotechnical Journal*, Vol 40, 209-220 (2003).

C.Gasiorek, S.Gould, A.Marchese, L.Skolmoski and K.R.Reddy, "Use of shredded tires and glass cullet as trench back fill," Report No.UIC-GGEL-95-06, University of Illinois at Chicago, USA, 1995.

M.A.Gebhardt, "Shear strength of shredded tires as applied to the design and construction of a shredded tire stream crossing, "MS thesis, Iowa state University, USA, 1997.

J.Hartlen Pressure Berms, Soil Replacement and Lightweight Fills, 3rd International Geotechnical Seminar, Soil Improvement Methods, Singapore pp101-111, 1985.

J.S.Horvath, "'Lite' products come of age: new developments in geosynthatics," ASTM Standardization news, pp.50-53, September 1992.

D.N.Humphrey and W.L. Nickels, "Tire Chips as Subgrade Insulation and Lightweight Fill", Presented at the: 18th Annual Meeting of the Asphalt Recycling and Reclaiming Association, Pompano Beach, Florida, USA, February 1994.

D.N.Humphery and W.P.Manion, "Properties of Tire Chips for Lightweight Fill." Proceedings of the Conference on Grouting, Soil Improvement, and Geosynthetics, ASCE, New Orleans, Louisiana, USA, Vol-2, pp. 1344-1355, 1992. D.N.Humphrey and T.C.Sandford, "Tire Chips as Lightweight Subgrade Fill and Retaining Wall Backfill", Submitted to: Symposium on Recovery and Effective Reuse of Discarded Materials and By-Products for Construction of Highway Facilities, Denver, CO, October 19-22, 1993.

D.N.Humphrey, T.C.Sandford, M.M.Cribbs, H.G.Gharegrat, and W.P.Manion, "Tire Chips as Lightweight Backfill for Retaining Walls – Phase 1 (Draft), A Study for the New England Transportation Consortium, August 1992.

B.Indraratna, A.S.Balasubramaniam and S.Balachandran "Performance of test embankment constructed to failure on soft marine clay" ASCE J Geotechnical engineering, vol.118, no.1, pp 12-33, 1992.

K.L. Johnson, "Contact Mechanics", Cambridge University Press, Cambridge, Great Britain, 1985.S.G. Lekhnitskii, "Theory of Elasticity of an Anisotropic Body", English Translation, Mir Publishers, Moscow, 1981.

W.A.Karunawardana "Improvement of peat by preconsolidation." A comparison of field and laboratory results. M.Eng thesis University of Moratuwa, 2002.

R.Kugan, "Peaty clay improvement with vertical drains" M.Sc thesis University of Moratuwa, 2004.

J.H.Lee, R. Salgado, A. Bernal and C.W. Lovell, "Shredded Tires and Rubber-Sand as Lightweight Backfill." Journal of Geotechnical and Geoenvironmental Engineering, ASCE, 125, No.2, 132-141, 1999.

Maior 1992, reference from, D.M.Potts and L.Zdravkovic "Finite element analysis in geotechnical engineering" application, Imperial College, UK.

P.Manion and D.N.Humphrey, "Tire Chips as Lightweight and Conventional Embankment Fill, Phase 1-Laboratory", A Study for the Maine Dept. of Transportation, Minnesota Pollution Control Agency, 1992.

E.Masad, T.Ramzi and H.Carlton "Engineering properties of Tire/soil Mixtures as a Light weight Fill Material", 1990.

E.M.Masad, R.Taha, and T.Papagiannakis, "Engineering properties of tyre/toil mixtures as a lightweight fill material," Geotechnical Testing Journal, GTJODJ, Vol.19, No.3, Sept.1996, pp.297-304, 1996.

E.J.Monahan, "Weight credit foundation construction using artificial fills," Transportation research board, 72nd Annual meeting, Washingston, DC, 10-14 January 1993.

D.E.Newcomb and A.Drescher, "Engineering Properties of Shredded Tires in Lightweight Fill Applications", *Transp.Res.Rec*, 1437, 1-7, National Academy Press, Washington, DC, 1994.

D.Nightingale and W.Green, "An unsolved riddle; Tire chips, two road beds, and spontaneous reactions," ASTM, west Conshohocken, Pa, 265-285,1997.

D.Negussey and M.Jahanandish, "A comparison of some engineering properties of EPS to soils," 72nd Annual meeting, Washingston, DC, 10-14 January 1993.

J.Read, T.Dodson, and J.Thomas, "Experimental Project Use of Shredded Tires for Lightweight Fill", Oregon Department of Transportation, Prepared for Federal Highway Administration, Washington, DC, February 1991. K.R.Reddy and R.A.Saichek, "Use of shredded scrap tires as landfill liner protective cover and leachate drainage layer material," Report No. UIC-GGEL-97-02, University of Illinois at Chicago, 1998.

N.J.O.Riordan and J.W.Seaman, Contractor Report No 341, Transport Research Laboratory, "Highway embankments over soft compressible alluvial deposits", guide for design and construction, 1994.

K.H.Roscoe, & J.B.Burland, "Generalised stress-strain behaviour of 'wet' clay, In *Engineering Plasticity* (eds J. Heyman & F. A. Leckie), pp. 535-609,UK.

K.H.Roscoe, A.N.Schofield, & A.Thurairajah, Yielding of clays in states wetter than critical. *Géotechnique* 13, No. 3, pp211-240, 1963.

SAGE CRISP version 4 technical reference manual, 1996.

G.N.Smith, "Elements of soil mechanics" 6th edition, published by BSP professional books, 1990.

S.P.Soupir, "Use of Alternative Backfill Designs for Integral Abutment Bridge End Treatment", Proceedings of the 46th Annual Geotechnical Engineering Conference, St.Paul, MN, 1998.

P.Tavenas, S.Leroueil, "The permeability of natural soft clay," Part 11: permeability characteristics. Canadian Geotechnical Journal, 20:pp645-660, 1983.

J.J.Tweeedie, D.N.Humphrey and T.C.Sanford, "Full-scale field trials of tire chips as lightweight retaining wall backfill, at rest conditions", Transportation research record No.1619, pp64-71, 1998.

R.J.Upton, J.Thomas, R.Kobernik, "Experimental Project Use of Shredded Tires forLightweight Fill", FWHA Experimental Project No. 1, DTFH-71-90-501-OR-11, FinalMonitoring Report, Oregon Department of Transportation, Prepared for Federal HighwayAdministration, Washington, DC, September 1992.

R.J Upton, and G.Machan, "Use of shredded tyres for light weight fill," Light weight artificial and waste material for embankments over soft soils, transportation Research record, no 1422, national academy press, Washington, DC, pp.36-45, 1993.

L.J.Wardle, "Program CIRCLY - A Computer Program for the Analysis of Multiple Complex Circular Loads on Layered Anisotropic Media – User's Manual", Geomechanics Computer Program No. 2, CSIRO Division of Applied Geomechanics, 1976.

W.Y. Wu, C.C. Benda, and R.F. Cauley, "Triaxial Determination of Shear Strength of Tire Chips", J. of Geotech. and Geoenv. Engrg., Vol. 123, No. 5, ASCE, May 1997.

C.P.Wroth, & G.T.Houlsby, "Soil mechanics – property characterisation and analysis procedures," XI Int. Conf. Soil Mechanics and Foundation Engineering, San Francisco, pp. 1–55. 1985.

