

PREPARATION AND CHARACTERIZATION OF LOW DENSITY  
POLYETHYLENE-BASED COMPOSITE MATERIALS CONTAINING  
RICE-STRAW AS A FILLER



by

S. S. Dodampegamage

66 "04"  
66.022.32 (669.018.672)

This Thesis was submitted to Department of Chemical and Process Engineering of  
the University of Moratuwa in partial fulfillment of the requirement for the Degree  
of Master of Science in Polymer Technology

Department of Chemical and Process Engineering  
University of Moratuwa

Sri Lanka,

2004

University of Moratuwa



82548

82548

82548

Thesis



## DECLARATION

---

I hereby declare that this submission is a result of a work carried out by me and to the best of my knowledge, it contain no material previously written or published by another person nor material which has been accepted for the award of any degree or acceptable qualification of a university, or other Institute of higher learning, except where the due reference to the material is made.




(S. S. Dodampegamage)

December 21 2004



University of Moratuwa, Sri Lanka  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)

To the best of my knowledge, the above particulars are correct.



(Dr. B A J K Premachandra)

## ABSTRACT

---

This thesis consists of four chapters. Chapter one contains an introductory part including scope and the objectives of the research. Since the present research is divided in to three major parts, chapter two, three and four are arranged accordingly. Each chapter includes an introduction discussing the relevant literature, the experimental work, results and discussions and finally, the conclusions drawn. The contents of this thesis can be best summarized as follows.

### **Preparation and characterization of composite materials containing LDPE and untreated rice-straw powder**

A series of Low Density Polyethylene (LDPE)/straw composites containing different amount of straw (as wt %) were prepared using rice-straw powder having three different particle sizes (50  $\mu\text{m}$ , 90  $\mu\text{m}$  and 250  $\mu\text{m}$ ). Mixing was done by melt-mixing technique, where LDPE and straw powder were mixed in a Brabender plasti-corder, which was operating at 170°C temperature and 60 rpm. The composites were studied by using Fourier Transform Infra-red spectroscopy (FTIR). The failure modes, tensile properties, water absorption, biodegradation and weatherability were investigated as a function of the weight percentage as well as particle size of straw filler in the composite. It was found that the incorporation of straw into LDPE matrix has reduced the ductility of the composite. The mechanical properties of the composites, especially the tensile strength and elongation at break were significantly low compared to those of neat LDPE. A significant improvement in modulus was shown by the composites. It was found that the tensile properties were depended on the amount and particle size of the straw in a composite.

Biodegradability of cellulose component in the rice-straw and LDPE-straw composites, after exposure to cellulase enzyme solution, was assessed by weight loss measurements. It was found that rice-straw sample is readily biodegradable but degradability of the composite samples was not significantly affected by the cellulase enzyme.

The extent of degradation after the weathering process was assessed by the loss of tensile strength measurements of the composites after incubation of the samples in a weather meter, which was at 70<sup>o</sup> C and continuous UV and moisture cycles for five days. It was found that the degradability of the composite samples depends on the amount of the rice-straw in a sample.

### **Preparation and characterization of maleic anhydride grafted LDPE and composite materials with maleic anhydride grafted LDPE and untreated rice straw**

A series of maleic anhydride grafted LDPE samples with different wt%'s of maleic anhydride and dicumyl peroxide were prepared and studied. The maleic grafted LDPE samples were prepared by melt free radical grafting method, where the grafting reaction of LDPE was carried out with the free radical initiator (Dicumyl peroxide) in a Bra-bender PL2000 plasti-corder operating at 170 ° C. Fourier transform infrared (FTIR) spectroscopy confirmed the grafting of maleic anhydride on LDPE backbone. Melt viscosity measurements and tensile measurements of grafted LDPE samples confirmed the unwanted cross- link formation during the grafting reaction.

A series of composites with maleic grafted LDPE and different composition of untreated rice-straw were prepared using simultaneous grafting and mixing technique. In this regard LDPE, maleic anhydride, dicumyl peroxide and rice-straw were fed in to the hot plasti-corder operating at 170<sup>o</sup> C, where melt free radical grafting reaction as well as melt mixing of straw filler with LDPE were occurred. Fourier transform infrared (FTIR) spectroscopy confirmed the formation of new interface interaction (ester bond) between the rice-straw and maleic grafted LDPE. The failure modes, mechanical properties, rheological properties, water absorption, biodegradation and weatherability were investigated with respect to the weight percentage of the straw as well as particle size of the straw in the composite sample. Improved mechanical properties, especially tensile strength and modulus were also evidenced the compatibility and interface interaction in the maleated LDPE-straw composites. It was found that the tensile and modulus values of maleated LDPE-straw composites having smaller particle size and higher filling level of rice-straw

to be higher due to the formation of more interactions at the interface. According to the melt viscosity and shear rate analysis, higher melt viscosity was shown by the maleated LDPE-straw composites due to the undesirable cross-links formed in the maleation process. Compared to the LDPE-straw composites, the corresponding maleated LDPE-straw composites have shown higher water absorption. As in the case of LDPE-straw composite these composites also have not shown any weight loss after the digestion with cellulase enzyme but have shown a considerable degradability after the weathering process.

### **Preparation and characterization of composite materials with maleated LDPE and treated rice-straw**

Using simultaneous grafting and mixing technique, another series of composites were prepared with maleated LDPE and treated rice-straw powder. In order to remove lignin and other waxy substances, rice-straw was subjected to steam explosion and hot alkyl treatments. By the chemical analysis results it was found that most of the lignin and other waxy substances have removed from the straw surface. Fourier transform infrared (FTIR) spectroscopic results also confirmed the removal of lignin and thereby increase of wt% of cellulose in rice-straw. Further FTIR analysis of the composite sample more clearly showed the formation of interface ester linkages between the treated straw and maleated LDPE.

Similar to the chapter three, different property analysis such as mechanical, water absorption, enzymatic digestion and weatherability were carried out with respect to the weight percentage and particle size of the straw filler. Compared to the LDPE-straw composites and maleated LDPE-untreated straw composites, significant improvement in the mechanical properties were resulted in the maleated LDPE-treated straw composites. It was also evidenced that the removal of lignin by the treatment processes has enhanced the interface interaction of maleated LDPE-straw system. Further it was found that filler properties such as the amount of straw filler in the composite and the particle size of straw also govern the mechanical properties of the composites. Providing more surface area and more OH groups to form ester bonds, composites having smaller size and higher amount of straw have shown higher tensile and modulus values. Also in this series the percentage elongation properties were significantly reduced with the introduction of the treated straw in to

LDPE but the reduction is significantly lower than the composites with maleated LDPE-untreated straw. The extent of the biodegradability of the composites with cellulase enzyme was also analyzed by the weight loss measurements. As in the above two composite series maleated-treated composites also have not shown significant digestion with the cellulase enzyme.



University of Moratuwa, Sri Lanka.  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)



## ACKNOWLEDGEMENTS

---

I wish to express my deepest gratitude to my supervisor, to whom I am deeply indebted, Dr Jagath K Premachandra, Department of Chemical and Process Engineering, University of Moratuwa. His attentiveness and interest in this study, advice and criticism have motivated me immensely and guided me on the pathway to the successful completion of this work.

I would like to express my deep gratitude to Dr. Shantha Walpalage, Head of the Polymer Division, Department of Chemical and Process Engineering, University of Moratuwa for his kind co operation given to me on completion of this work. Further I would like to acknowledge Dr. (Mrs.) Chandima K. Jayasuriya, Department of Chemistry, University of Kelaniya and Mr. S. A. S. Perera, Department of Chemical and Process Engineering, University of Moratuwa, for their helpful ideas, advices given to complete this work successfully.



Electronic Theses & Dissertations  
www.lib.mrt.ac.lk

I would like to acknowledge Dr. Gamini Senevirathna, Deputy Director Research (Technology), Rubber Research Institute, Mrs. Dilhara Edirisinghe, for their kind assistance in granting me to carryout practical in their institute premises. I render my heartiest gratitude and special thank to Mr. H. N. K. K. Chandralal, Mr. L. G. P. Lelwela and Mrs. Manel Mahanama, for their immense co operation and assistance towards my research and further, acknowledge all staff members and technical officers of Rubber Research Institute, Ratmalana, for their kind co operation.

My deep gratitude goes to Dr. N. Munasinghe, Head of the Materials Engineering Department, University of Moratuwa, for his kind assistance in granting me to use laboratory equipments in his department. I further, extend my gratitude and special thank to the academic staff member Mr. V. S. C. Weragoda and the senior staff technical officer, Mr. Sarath Chandrapala for their immense co operation and assistance towards my research work.

I further, acknowledge Dr. Sudantha Liyanage, Head of the Polymer Division, Department of Chemistry, University of Sri Jayawardenapura for granting me permission to use laboratory facilities in the department. I acknowledge with special thanks to the Technical officer Mr. Sagara Dias, for his immense assistance given to me.

I further extend my deep gratitude to Dr. (Mrs.) Padma Amarasinghe, Department of Chemical and Process Engineering, University of Moratuwa, all academic staff and the laboratory staff of the department for their support in numerous ways, for which I will always be thankful. I will be indebted to Asian Development Bank for granting financial assistance for the course of study.

Finally, I acknowledge with heartiest gratitude to my husband and my best friends Gayani and Manju who supported me in numerous ways, which motivated me to complete this work successfully.



University of Moratuwa, Sri Lanka  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)




## TABLE OF CONTENTS

Page No.

---

<b>Declaration</b>	i
<b>Abstract</b>	ii
<b>Acknowledgements</b>	iv
<b>Table of contents</b>	viii
<b>List of Tables</b>	xiv
<b>List of Figures</b>	xv
<b>List of abbreviations</b>	xx
<b>CHAPTER ONE – BACKGROUND MOTIVATION</b>	1
1.1 Background motivation	2
1.2 Objectives	5
<b>CHAPTER TWO – PREPARATION AND CHARACTERIZATION OF LDPE -STRAW COMPOSITES</b>	6
<b>2.1 INTRODUCTION</b>	7
2.1.1 Polymer composites	7
2.1.2 Lignocellulosic fillers	9
2.1.3 Chemical composition of lignocellulosic materials	10
2.1.4 Rice-straw as a filler	12
2.1.5 Degradation of rice-straw	13
2.1.6 Enzymatic degradation of cellulose	14
2.1.7 Advantages and disadvantages of straw as a filler	16

<b>2.2 THEORIES ON THE EFFECT OF FILLERS ON THE FAILURE MODES AND MECHANICAL PROPERTIES OF A COMPOSITE</b>	19
2.2.1 The effect of fillers on the failure modes of a polymeric composite	19
2.2.2 The effect of fillers on extension	20
2.2.3 The effect of fillers in tensile strength of a polymeric composite	20
2.2.4 The effect of fillers in modulus of a composite	22
<b>2.3 EXPERIMENTAL</b>	24
2.3.1 Materials	24
2.3.2 Preparation of the straw powder	24
2.3.3 Preparation of composites with LDPE and straw powder	24
2.3.4 FTIR analysis of LDPE and PES composites	25
2.3.5 Determination of the tensile properties of the PES composites	25
2.3.6 Determination of the water absorptivity and biodegradability of PES composites	25
2.3.7 Determination of the weatherability of PES composites	26
<b>2.4 RESULTS AND DISCUSSION</b>	27
2.4.1 Analysis of FTIR spectra of PES composites	27
2.4.2 Tensile properties of PES composites	30
2.4.2(a) Failure modes of PES composites	30
2.4.2(b) Tensile properties of PES composites	38
2.4.3 Water absorption and biodegradability of PES composites	44
2.4.4 Determination of the weatherability of PES composites	48
<b>2.5 CONCLUSIONS</b>	50



<b>CHAPTER THREE – PREPARATION AND CHARACTERIZATION OF MALEIC ANHYDRIDE GRAFTED LDPE AND MALEATED LDPE-STRAW COMPOSITES</b>	51
<b>3.1 INTRODUCTION</b>	52
<b>3.2 EXPERIMENTAL</b>	58
<b>3.2.1 PREPARATION AND CHARACTERIZATION OF MALEIC ANHYDRIDE GRAFTED LDPE</b>	58
3.2.1.1 Materials	58
3.2.1.2 Recrystallization of maleic anhydride	58
3.2.1.3 Preparation of maleic anhydride grafted LDPE (maleated LDPE)	58
3.2.1.4 Spectroscopic analysis of maleated LDPE	59
3.2.1.5 Analysis of rheological properties of LDPE and maleated LDPE change with maleation (Rheological analysis of LDPE and different maleated LDPE samples)	59
3.2.1.6 Determination of the tensile properties of different maleated LDPE samples	59
<b>3.2.2 PREPARATION AND CHARACTERIZATION OF COMPOSITE MATERIALS WITH MALEIC ANHYDRIDE GRAFTED LDPE AND RICE STRAW</b>	60
3.2.2.1 Materials	60
3.2.2.2 Preparation of composite samples with maleic anhydride grafted LDPE and rice-staw	60
3.2.2.3 Determination of the tensile properties of MPES composite samples	61
3.2.2.4 FTIR analysis of MPES composite samples	61

3.2.2.5 Analysis of rheological properties of MPES composites	61
3.2.2.6 Determination of the water absorptivity and biodegradability of MPES composites	61
3.2.2.7 Determination of weatherability of MPES composites	61
<b>3.3 RESULTS AND DISCUSSION</b>	<b>62</b>
<b>3.3.1 PREPARATION AND CHARACTERIZATION OF MALEIC ANHYDRIDE GRAFTED LDPE</b>	<b>62</b>
3.3.1.1 Spectroscopic analysis of maleic anhydride grafted LDPE samples	62
3.3.1.2 Rheological analysis of LDPE and different maleated LDPE samples	62
3.3.1.3 Determination of the mechanical properties of the maleated LDPE samples	64
<b>3.3.2 PREPARATION AND CHARACTERIZATION OF COMPOSITE MATERIALS WITH MALEIC ANHYDRIDE GRAFTED LDPE AND RICE STRAW</b>	<b>66</b>
3.3.2.1 FTIR analysis of MPES composite and LDPE sample	66
3.3.2.2 Failure modes of MPES composites	69
3.3.2.3 Determination of Tensile properties of MPES composites	76
3.3.2.4 Analysis of rheological properties of MPES composites	82
3.3.2.5 Determination of the water absorptivity and biodegradability of MPES composites	82
3.3.2.6 Determination of weatherability of MPETS composite samples	84
<b>3.4 CONCLUSIONS</b>	<b>87</b>

<b>CHAPTER FOUR - PREPARATION AND CHARACTERIZATION OF COMPOSITE MATERIALS WITH MALEIC ANHYDRIDE GRAFTED LDPE AND TREATED RICE STRAW</b>	<b>88</b>
<b>4.1 INTRODUCTION</b>	<b>89</b>
<b>4.2 EXPERIMENTAL</b>	<b>92</b>
4.2.1 Materials	92
4.2.2 Modification of rice-straw by mercerization and steam explosion methods	92
4.2.3 FTIR spectral analysis of treated straw powder and untreated straw powder.	93
4.2.4 Chemical analysis of components of straw powder samples before and after treatments	93
4.2.5 Preparation of maleic anhydride grafted LDPE-treated rice-straw composites	93
4.2.6 FTIR spectral analysis of MPETS composites and MPES composites	94
4.2.7 Determination of tensile properties of the MPEST composites	94
4.2.8 Determination of the water absorptivity and biodegradability of MPETS Composites	94
4.2.9 Determination of weatherability of MPETS composites	94

<b>4.3 RESULTS AND DISCUSSION</b>	
4.3.1 FTIR spectral analysis of untreated straw powder and treated straw powder	95
4.3.2 Chemical analysis of the components of straw powder samples before and after the treatments	95
4.3.3 FTIR spectral analysis of MPETS composites and MPES composite samples	96
4.3.4 Analysis of failure modes of MPETS composites	98
4.3.5 Determination of tensile properties	98
4.3.6 Water absorption and biodegradability of MPETS composites	98
4.3.7 Determination of weatherability of MPETS composites	104 111
<b>4.4 CONCLUSIONS</b>	113
<b>CHAPTER FIVE</b>	114
5.1 FUTURE WORK	115
5.2 LIST OF REFERENCES	116



## LIST OF TABLES

---


	Page No
<b>Table 2.1</b> Different types of lignocellulosic fillers used in the polymeric composites	9
<b>Table 2.2</b> Infrared peak assignments for LDPE, straw powder and PES composite	28
<b>Table 2.3</b> Tensile properties of LDPE and PES composites	39
<b>Table 2.4</b> Variation in tensile properties of LDPE and PES composites after weathering process	48
<b>Table 3.1</b> Tensile properties of different maleated LDPE samples.	66
<b>Table 3.2</b> Infrared vibrations and assignment for PES composite, maleated LDPE and MPES composite	67
<b>Table 3.3</b> Tensile properties of maleic grafted LDPE and MPES composites	76
<b>Table 3.4</b> Variation in tensile properties of MPES composites after weathering process	85
<b>Table 4.1</b> Infrared vibrations and assignment for straw powder	95
<b>Table 4.2</b> Chemical analysis of components in rice-straw	96
<b>Table 4.3</b> Tensile properties of maleic grafted LDPE and MPETS composites	103
<b>Table 4.4</b> Variation in tensile properties of MPETS composites after weathering	112


## LIST OF FIGURES

---

	Page No.
<b>Figure 1.0</b> Schematic representation of cellulose	11
<b>Figure 1.1</b> Schematic representation of hemicellulose	11
<b>Figure 1.2</b> Schematic representation of three basic building blocks of lignin	12
<b>Figure 2.0</b> FTIR spectra of a) Rice Straw b) LDPE c) PES composites	29
<b>Figure 2.1 (a)</b> Stress-strain curve for LDPE	31
<b>Figure 2.1 (b)</b> Stress-strain curves for (◆) PES-50-5, (●) PES-50-10 and (▲) PES-50-15 composites	32
<b>Figure 2.1 (c)</b> Stress-strain curves for (◆) PES-90-5, (●) PES-90-10 and (▲) PES-90-15 composites	33
<b>Figure 2.1 (d)</b> Stress-strain curves for (◆) PES-250-5, (●) PES-250-10 and (▲) PES-250-15 composites	34
<b>Figure 2.2 (a)</b> Stress-strain curves of different PES composites having 5%wt of straw. (◆) PES-50-5, (●) PES-90-5 and (▲) PES-250-5 composites	35
<b>Figure 2.2 (b)</b> Stress-strain curves of different PES composites having 10 %wt of straw. (◆) PES-50-10, (●) PES-90-10 and (▲) PES-250-10 composites	36



<b>Figure 2.2 (c)</b> Stress-strain curves of different PES composites having 15 %wt of straw. (◆) PES-50-15, (●) PES-90-15 and (▲) PES-250-15 composites	37
<b>Figure 2.3 (a)</b> Variation in tensile strength vs straw content for (◆) PES-50, (●) PES-90 and (▲) PES-250 composites	38
<b>Figure 2.3 (b)</b> Variation in % elongation vs straw content for (◆) PES-50, (●) PES-90 and (▲) PES-250 composites	39
<b>Figure 2.3 (c)</b> Variation in Young's modulus vs straw content for (◆) PES-50, (●) PES-90 and (▲) PES-250 composites	40
<b>Figure 2.4</b> Percentage weight change of (◆) PES-50-5, (■) PES-50-15, (*) PES-90-15 and (●) PES-250-15 composites during immersion in water	46
	
<b>Figure 3.0</b> Schematic representation of Maleic anhydride	53
<b>Figure 3.1</b> Decomposition reaction of DCP	54
<b>Figure 3.2</b> Formation of LDPE macro radical	54
<b>Figure 3.3</b> Grafting of maleic anhydride on LDPE backbone	55
<b>Figure 3.4</b> Transferring step of macro radical in to LDPE backbone	55
<b>Figure 3.5</b> Formation of covalent interaction between maleated LDPE and OH of cellulose	57
<b>Figure 3.6</b> FTIR spectra of Maleic anhydride grafted LDPE and virgin LDPE	63

<b>Figure 3.7</b> Melt viscosity and shear rate behavior of (■) LDPE, (●) LDPE + 0.05% DCP + 5% MA, (▲) LDPE+ 0.25% DCP + 5% MA, (□) LDPE + 0.4% DCP+5% MA and (◆) LDPE + 0.4% DCP samples	65
<b>Figure 3.8</b> FTIR spectra of (a) Maleic anhydride grafted LDPE, (b) PES composite and (c) MPES composite	68
<b>Figure 3.9(a)</b> Stress-strain curves for (◆) MPES 50-5, (●) MPES 50-10 and (▲) MPES 50-15 composites	70
<b>Figure 3.9(b)</b> Stress-strain curves for (◆) MPES 90-5, (●) MPES 90-10 and (▲) MPES 90-15 composites	71
<b>Figure 3.9(c)</b> Stress-strain curves for (◆) MPES 250-5, (●) MPES 250-10 and (▲) MPES 250-15 composites	72
 <small>University of Moratuwa, Sri Lanka Electronic Theses &amp; Dissertations www.lib.mrt.ac.lk</small>	
<b>Figure 3.10(a)</b> Stress-strain curves of different MPES composites having 5%wt of straw. (◆) MPES-50-5, (●) MPES- 90-5 and (▲) MPES-250-5 composites	73
<b>Figure 3.10(b)</b> Stress-strain curves of different MPES composites having 10 %wt of straw. (◆) MPES-50-10, (●) MPES-90-10and (▲) MPES-250-10 composites	74
<b>Figure 3.10(c)</b> Stress-strain curves of different MPES composites having 15 %wt of straw (◆) MPES-50-15, (●) MPES-90-15and (▲) MPES-250-15 composites	75
<b>Figure 3.11(a)</b> Variation in tensile strength vs straw content for (◆) MPES-50, (●) MPES-90 and (▲) MPES-250 composites	79

<b>Figure 3.11(b)</b> Variation in Young's modulus vs straw content for (◆) MPES-50, (●) MPES-90 and (▲) MPES-250 composites	80
<b>Figure 3.11(c)</b> Variation in % elongation vs Straw Content for (◆) MPES-50, (●) MPES-90 and (▲) MPES-250 composites	81
<b>Fig 3.12</b> Melt viscosity and shear rate behavior of MPES composite (◆) MPES 50-15 and (■) PES50-15 composite	83
<b>Fig 3.13</b> Percentage weight change of (□) MPES 50-5, (■) MPES 50-15, (*) MPES 90-15 and (●) MPES 250-15 composites during immersion in water.	86
<b>Figure 4.0</b> FTIR spectra of (a) Treated Straw and (b) Untreated Straw	97
<b>Figure 4.1</b> FTIR spectra of (a) MPETS and (b) MPES Composite	99
<b>Figure 4.2(a)</b> Stress-strain curves for (◆) MPETS 50-5, (●) MPETS 50-10 and (▲) MPETS 50-15 composites	100
<b>Figure 4.2(b)</b> Stress-strain curves for (◆) MPETS 90-5, (●) MPETS 90-10 and (▲) MPETS 90-15 composites	101
<b>Figure 4.2(c)</b> Stress-strain curves for (◆) MPETS 250-5, (●) MPETS 250-10 and (▲) MPETS 250-15 composites	102
<b>Figure 4.3(a)</b> Variation in tensile strength vs straw content for (◆) MPETS-50, (●) MPETS-90 and (▲) MPETS-250 composites	105

<b>Figure 4.3(b)</b> Variation in Young's modulus vs straw content for (◆) MPETS-50, (●) MPETS-90 and (▲) MPETS-250 composites	106
<b>Figure 4.3(c)</b> Variation in % elongation vs straw content for (◆) MPETS-50, (●) MPETS-90 and (▲) MPETS-250 composites	107
<b>Figure 4.4(a)</b> Variation in tensile strength of different composites for (◆) PES 50 series, (●) MPES 50 series and (▲) MPETS 50 series composites	108
<b>Figure 4.4(b)</b> Variation in Young's modulus of different composites for (◆) PES 50 series, (●) MPES 50 series and (▲) MPETS 50 series	109
<b>Fig 4.5</b> Percentage weight change of (◆) MPETS 50-5, (■) MPETS 50-15, (*) MPETS 90-15 and (●) MPETS 250-15 composites during immersion in water	110

## LIST OF ABBREVIATIONS

---

CCl <sub>4</sub>	- Carbon tetra Chloride
CaCO <sub>3</sub>	- Calcium Carbonate
DCP	- Dicumyl Peroxide
DP	- Degree of Polymerization
FTIR	- Fourier Transform Infra- Red
KBr	- Potasium Bromide
HDPE	- High Density Polyethylene
LDPE/PE	- Low Density Polyethylene
MA	- Maleic Anhydride
MPa	- Mega Pascal
MPETS	- Maleated LDPE/Treated straw composite
MPES	- Maleated LDPE/Un Treated straw composite
NaOH	- Sodium hydroxide
PES	- LDPE/Un Treated rice-straw composite
PMPPIC	- Poly[methylene (poly (phenyl isocyanate))]
PP	- Polypropylene
PS	- Polystyrene
PVC	- Polyvinyl Chloride
rpm	- Rounds per minutes
TAPPI	- Technical Association for Pulp And Paper Industry
TDIC	- Toluene2, 4- diisocyanate
%T	- Percentage transmittance
UV	- Ultraviolet radiation
Wt %	- Weight percentage
3-D	- Three dimensional