THE STUDY OF BRIGHTNESS LEVELS OF HEADLIGHTS OF OPERATING VEHICLES IN SRI LANKA

Rathnayaka Mudiyanselage Sumedha Kasun Senarathna 138320X

M. Eng. in Highway and Traffic Engineering

Department of Highway and Traffic Engineering

University of Moratuwa

Sri Lanka

DECLARATION OF THE CANDIDATE AND SUPERVISOR

I declare that this is my own work and this thesis does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any University or other institute of higher learning and to the best of my knowledge and belief, it does not contain any material previously published or written by another person except where the acknowledgement is made in the text.

Also, I hereby grant the University of Moratuwa the non-exclusive right to reproduce and distribute my thesis, in whole or in part in print, electronic or other medium. I also retain the right to use this content in whole or part in future works (such as articles or books).

Signature:			Date:			
The above candidate has car supervision.	ied out research	for the	Master	thesis	under	my
Signature of the Supervisor:		Date:				

ACKNOWLADGEMENT

First of all, I wish to express my deepest gratitude to University of Moratuwa, Sri Lanka, for giving me the opportunity to follow this post-graduate programme at the Department of Civil Engineering, University of Moratuwa. I would also like to thank Dr. Dimatha De Silva and Mr. Loshaka Perera for giving me a chance to complete my study under their supervision. This dissertation would not have been a reality if not for their friendly guidance and shared knowledge.

I would also like to thank all staff of the Department of Highway and Traffic Engineering, University of Moratuwa including Prof. J.M.S.J. Bandara, Prof. W.K. Mampearchchi and Dr. H.R.Pasindu for giving me their valuable support during the academic sessions and in successful completion of the Master's Degree Course during past three year period. Special thanks go to my fellow students who helped me throughout this academic exploration.

Thanks also go to senior officers of the Road Development Authority at my working place, by granting me leave and encouraging me to complete this course successfully.

Finally, I would like to thank all my colleagues of the work place for supporting me in various ways to succeed my effort.

ABSTRACT

Driving an automobile is primarily a visual task, and vision contributes as much as 90% of the information required to drive (Alexander and Lunenfeld 1990). At night time, the required visibility level of roadway is created artificially by vehicle headlights or street lighting or both. Illuminating roadway using vehicle headlight is the most common method at night time driving, but too much light and improper lighting may result in glare, which causes visual discomfort and a diminished ability to see the roadway. In another way, insufficient light causes problems for drivers to see the information needed or potential hazards in the roadway.

There are many different kinds of headlight systems in operating vehicles (imported from various manufactures of various countries in various time periods) in Sri Lankan roads including the oldest systems and the most upgraded systems. Generally, a halogen headlamp system which is commonly found in Sri Lankan roads is expected to be performed well for about 10 years in normal conditions. But the percentage of older vehicles more than 10 years is higher in Sri Lankan roads.

Different organizations all around the world have introduced regulations on vehicle headlights not only for the vehicle manufactures but also for the drivers. Comparisons show that the current Sri Lankan regulations have not been updated to address the issues. Even though the road surfaces have been improved so that encouraging drivers to drive faster, other factors have not been considerably improved. Therefore, introducing of the new regulatory system should be considered to control this vast variety and mitigate the risk and un-comforting condition. The intention of this research is to identify brightness levels of operating vehicles in Sri Lankan roads based on Federal Motor Vehicle (USA) regulations which may helpful in above discomfort circumstances.

The experimental brightness levels of headlights were measured by simulating the testing arrangement at a work station free for night time. The readings were taken in terms of "Lux" and maximum and minimum levels of brightness were identified.

The results of field tests revealed that the majority of operating vehicles has less

brightness levels compared with the minimum brightness level specified in the

Federal Motor Vehicle Regulation. Vehicles older than five years were failing to

produce a sufficient intensity for low beam operation compared to the FMVSS

limitation. Further, it was revealed that the most headlights of operating vehicles are

miss-aimed and illuminate unnecessary regions which cause inconvenience to the

drivers of oncoming vehicles.

Also, it was revealed that the driver's attention to the maintenance of the headlight

system of their own vehicle is very poor.

Finally, this research suggests introducing regulations to minimize or mitigate

adverse effects of headlights by periodically evaluating headlight systems of

operating vehicles based on a proper regulator system in Sri Lanka.

Key words: Headlight, High beam, Low beam, Illumination

iv

TABLE OF CONTENT

Declaration of the Candidate and Supervisor	i
Acknowladgement	ii
Abstract	iii
Table of Content	v
List of Figures	vii
List of Tables	ix
List of Abbreviations	X
1 Introduction	1
1.1 Background of the Study	1
1.2 Objective	2
2 Literature Survey	
2.1 History of the headlamp regulation	
2.2 Relationship between glare and driving performance	
2.2.1 Spectrum	
2.2.2 Size of Headlamp	
2.2.3 Method followed	
2.3 Vehicle equipment and inspection regulations, Department	of
Transportation, Commonwealth of Pennsylvania (PUB-45)	
2.4 United Nations UNECE Regulation for vehicle manufactures, Regula	ation
No. 113	8
Source: UNECE Regulation for Vehicle Manufactures, Regulation No. 113	10
2.5 Official Manual For Vehicle Inspection, State of Rhode Island, USA	10
2.6 Vehicle inspection guidance, North Carolina	11
2.7 Motor Vehicle Safety Inspection Manual, Safety Division, Virginia S	State
Police 13	
2.8 Federal Motor Vehicle Safety Standard 108	16

	2.9	Me	easuring light	17
	2	2.9.1	Luminous intensity, the Candela	17
	2	2.9.2	Luminous power: Lumens	17
	2	2.9.3	Luminance: Candela per square meter	18
	2	2.9.4	Illuminance: Lux	18
	2	2.9.5	Summary	18
3	N	Measur	ring Brightness Of Headlamps Of Operating Vehicles In Sri Lanka	19
	3.1	Int	roduction	19
	3.2	Lo	cation and setup	20
	3	3.2.1	Lux meter	21
	3.3	Tes	st procedure	22
	3.4	Tes	st results	25
	3	3.4.1	Sample result 1: Test 3	25
	3	3.4.2	Sample result 2: Test 4	26
	3.5	Ob	servations	29
4	5	Summa	ary And Analsis Of Experimental Results	33
	4.1	Spe	ecification Requirements	33
	4.2	Co	mparison of brightness levels of operating vehicles in Sri Lanka	with
	FM	IVSS s	tandards.	33
	4.3	Illu	minance intensity variation with manufacturing year of vehicle	35
5	Con	clusio	ns, Recommendations And Suggestions	36
	5.1	Co	nclusions	36
	5.2	Re	commendations	36
	5.3	Sug	ggestions	36
D	- cc-	rnoo I	int	20

LIST OF FIGURES

Figure 2-1 Development of Headlamp Technology5
Figure 2-2 Instrumental setup followed in finding relation between glare and driving
performance7
Figure 2-3 Headlight aiming screen at 25 feet and inspection limits
2-4 Measuring Screen, test points and related illumination limits
3-1 Marking guidelines and preparing ground surface
3-2 Marking guidelines and preparing ground surface
Figure 3-3 Equipement used in field tests. 21
Figure 3-4 Operating instructions of the Lux meter
Figure 3-5 Recording primary details
Figure 3-6 Measuring illuminance intensities using Lux meter
Figure 3-7 Photograph of low beam operation Test No:3, The cutoff line can be
clearly observed
Figure 3-8 Illuinance intensity distribution of headlight in low beam operation:Test 3
Figure 3-9 Photograph of low beam operation Test No:4, The cutoff line is slightly
unclear and illuminance intensity is low by visual inspection
Figure 3-10 Illuinance intensity distribution of headlight in low beam operation:Test
4
Figure 3-11 Clear cutoff line and higher brightness emitting Test No 32
Figure 3-12 Hot Spot area
Figure 3-13 Light distribution of Test No 10, Total beam distribution has lowered
due to poor aiming
Figure 3-14 Light distribution of Test No 2, Scattered beam due to poor aiming 30
Figure 3-15 Light distribution of Test No 6, Poor llumnance intensity and Poor
aiming
Figure 3-16 Light distribution of Test No 9, VeryPoor llumnance intensity and Very
Poor aiming, Recently faced with an accident
Figure 3-17 Low beam distribution of pattern of 2 stroke three wheeler
Figure 3-18 Low beam distribution of pattern of Disel three wheeler

Figure 3-19 Low beam distribution pattern of Test No:8, Hot spot a	area found at
above from the horizontal centerline RHS	32
Figure 4-1 Comparison of brightness levels of all test vehicles in	with FMVSS
standards	34
Figure 4-2 Average Illuminance intensity arranged in order by manufact	turing year of
passenger cars	35

LIST OF TABLES

Table 3-1 Calculated Minimum and Maximum values(In Lux) as per FMVSS	and
Pennsylvanian Standards	20
Table 3-2 The list of test vehicles	24
Table 3-3 Test result values obtained(In Lux) after Test 3	25
Table 3-4Test result values obtained(In Lux) after Test 4	27

LIST OF ABBREVIATIONS

FMVSS Federal Motor Vehicle Safety Standards

UNECE United Nations Economic Commission for Europe

CMVSS Canada Motor Vehicle Safety Standard

LHS Left Hand Side

RHS Right Hand Side

GRE Group Rapporteurs Eclairage

US United States

UN United Nations

HPSV High Pressure Sodium Vapor

HID High intensity Discharger