

**COST SAVINGS FROM ENHANCED NOISE  
REDUCTION BASED BOILER BLOWDOWN  
CONTROL FOR STATE PHARMACEUTICALS  
MANUFACTURING CORPORATION (SPMC)**

Priyalal Dilakshan Jayasundera

(148459N)

Degree of Master of Science (Electronics & Automation)

Department of Electronic and Telecommunication Engineering

University of Moratuwa

Sri Lanka

April 2019

**COST SAVINGS FROM ENHANCED NOISE  
REDUCTION BASED BLOWDOWN CONTROL FOR  
STATE PHARMACEUTICALS MANUFACTURING  
CORPORATION (SPMC)**



Priyalal Dilakshan Jayasundera

(148459N)

Thesis submitted in partial fulfillment of the requirements for the degree Master of  
Science in Electronics and Automation

Department of Electronic and Telecommunication Engineering

University of Moratuwa

Sri Lanka

April 2019

## **DECLARATION, COPYRIGHT STATEMENT AND THE STATEMENT OF THE SUPERVISOR**

“I declare that this is my own work and this thesis does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text”.

“Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books)”.

Signature:

Date: April 2019

The above candidate has carried out research for the Master’s Thesis under my supervision.

Name of the supervisor: **Dr. Upeka Premaratne**

Signature of the supervisor:

Date: April 2019

## **ABSTRACT**

Boilers are widely used in most of the processing industries like Pharmaceuticals Manufacturing, for the heating applications. State Pharmaceuticals Manufacturing Corporation (SPMC) is the one of the largest Pharmaceuticals Manufacturing Plant in Sri Lanka. In Pharmaceuticals Industries Boiler is mainly used for the steam generation. In an industry normally a 4% of heat energy [1] is wasted through Blowdown.

For every Boiler there is a defined limits allowable TDS in the Boiler Drum. The Boiler feed water has a certain TDS. The maximum allowable TDS in process Boilers is 3500 ppm.

The steam is generated from the Boiler the TDS contained in the Boiler drums starts to increase. Therefore some amount of the high TDS water needs to be removed from the Boiler drum. This removal of high TDS water from the Boiler drum is called blowdown. By doing Boiler blowdown able to maintain the TDS in the Boiler drum to its optimal desired levels.

The process of blowdown is that most of the time the blowdown is done by manually. Therefore that extract amount of blowdown required is never done. Many times excess of blowdown is done and many times sub optimal blowdown is done both these are harmful. Excess amount of blowdown contributes to the blowdown loss.

Automatic blowdown control system sensors the actual TDS level in the Boiler drum and does the blowdown only when it is required to do so.

When the TDS level in the Boiler go beyond desired set point the blowdown valve will opens and brings down the TDS to the desired level.

High TDS level in the Boiler drum not only cause scaling within the Boiler drum and on the Boiler tubes. But these scales particles also get carried away with the steam and formed deposits on the downstream equipment and piping.

High TDS levels in the Boiler drum also results in moisture carryover which means steam coming out of the Boiler has a high moisture contained and this is detrimental

to the equipment downstream of the Boiler. It also results poor heat transfer in the process equipment and cause high steam consumption.

An automatic blow down control can keep the blow down rate uniformly close to the maximum allowable dissolved solids level, while minimizing blow down and reducing energy losses.

The Boiler Blowdown analysis and energy savings analysis has been carried out at SPMC Plant. The objective of this research work is the blowdown analysis in the plant and analyze the annual savings obtained from Automatic Blowdown Control Intervention. The study was revealed that changing from manual blowdown control to automatic blowdown control monitory savings **Rs 202873.11** a boiler's energy use by annually. Purchasing TDS sensor, pneumatic blowdown valve, PLC and related accessories fabrication cost can be a 3 year payback period on the investment.

## **ACKNOWLEDGEMENT**

I owe my profound gratitude to my supervisor, Dr. Upeka Premaratne; who has always been at the forefront, extending relentless guidance by way of providing much needed supervision throughout the research. I am also heartily thankful to course coordinator of the MSc programme in Electronics and Automation; Dr. Chamira U.S. Edussoriya for his precious advices on related technical and nontechnical topics throughout the research. Additionally, I want to acknowledge the course assistant; Mr. Damith Kandage for providing timely needed assistant on various matters from the start to successful completion of the thesis. Finally, I would like to thank all the academic staff members, supportive staff and undergraduate students who supported me throughout the research by way of extending kind hands, whenever necessary.

Wing Commander (Retd) Priyalal Dilakshan Jayasundera  
BSc (E & E) Eng (KDU), PG Dip in HRM (Colombo),  
MIET (UK), MIEEE (USA), MRAS (UK)  
Deputy General Manager Engineering  
State Pharmaceuticals Manufacturing Corporation of Sri Lanka  
No 11, Sir John Kotelawala Mawatha, Ratmalana.

April 2019.

# TABLE OF CONTENTS

DECLARATION, COPYRIGHT STATEMENT AND THE STATEMENT OF THE SUPERVISOR.....	i
ABSTRACT.....	ii
ACKNOWLEDGEMENT .....	iv
LIST OF FIGURES .....	vii
LIST OF TABLES.....	x
CHAPTER 1 .....	01
INTRODUCTION .....	01
1.1 Background Motivation .....	02
1.2 Problem Definition .....	03
1.2.1 Thesis Definition and Objectives.....	03
1.2.2 Goals .....	04
1.3 Limitations .....	04
1.4 Contribution to the SPMC.....	04
1.5 Repot Outline .....	05
CHAPTER 2 .....	06
LITERATURE REVIEW .....	06
2.1 Understanding Boiler Blow down.....	06
2.2. Boiler Blowdown Benefits .....	07
2.3. Best Operating for Boiler Blowdown.....	07
2.4. TDS Measurment Conductivity Method .....	08
2.5 The Maximum Recommended Concentration Limits .....	08
2.6 Manual Vs Automatic Blowdown.....	09
2.7 Calculating the blowdown rate.....	09
2.8 On/off Boiler Blowdown Valves.....	10
2.9 Closed Loop Electronic Control Systems .....	11
2.10. Manual Blowdown Controls .....	12
2.11. Automatic Blowdown Controls.....	13
2.12 Boiler Blowdown Analysis in an Industrial Boiler .....	16
2.13 Example Analysis of Blowdown Calculation .....	20
2.14 Evaluating Saving by Reducing Blowdown Rate .....	21
2.15 Boiler Blowdown Optimization Analysis .....	23

CHAPTER 3 .....	24
BOILER HOUSE BEHAVIOUR AT SPMC .....	24
3.1. Boiler House Parameter Observation .....	24
3.2. Overview of Boiler Steam Consumption Analysis .....	25
3.3. Present Manual Blowdown Practice of the Boiler House .....	26
3.4. Water TDS Level Analysis .....	37
3.5. Boiler Drum Water TDS Analysis .....	39
3.6. Boiler Feed Water TDS Analysis .....	33
3.7. Calculating Blowdown Quantity .....	34
3.8. Boiler Blowdown Optimization Calculation with Automation.....	34
3.9. Boiler Blowdown Energy Recovery Optimization Calculation at SPMC .....	35
3.10. Hypothetical Analysis TDS Control Effects for Energy Savings Boiler Blowdown Operation .....	37
CHAPTER 4 .....	43
MATHEMATICAL MODELING BOILER BLOWDOWN SYSTEM.....	43
4.1. Description of the System Model of Boiler Blowdown.....	43
CHAPTER 5 .....	49
MATLAB SIMULINK MODELING AND SIMULATION OF THE BOILER BLOWDOWN SYSTEM .....	49
5.1. Simulation and Modeling of the Boiler Blowdown Process .....	49
5.2. Modeling and Simulation TDS Sensor Noise and Disturbance Environment.....	512
5.3. Modeling and Simulation Removal of Noise of TDS Sensor .....	53
5.4. Real Data Simulation Develop Simulink Model.....	57
CHAPTER 6 .....	63
HARDWARE SELECTION AND CONTROL DESIGN.....	63
6.1 TDS Sensor Characteristics and Selection.....	63
6.1.1 Controlling Total Dissolved Solids in Boiler Water .....	63
6.1.2 Boiler Water Sampling.....	63
6.1.3 Conductivity Method .....	63
6.1.4 Conductivity Measurement in the Boiler .....	64
6.1.5 Cell Constant .....	65
6.1.6 Suitable TDS Measuring Sensor Selection .....	66
6.1.7 Suitable Blowdown Valve Selection for the System .....	69
6.2 Proposed Control Scheme .....	70
6.3 Development of Control Architecture.....	70



CHAPTER 7 .....	72
SYSTEM DESIGN AND HARDWARE IMPLEMENTATION .....	72
7.1 Introduction to Design .....	72
7.2 Designing of Control System .....	72
7.3 Selected Sensor and Puenmatic Valve Specifications .....	77
7.4 Hardware Fabrication and Installation of Main Control Panel Board .....	78
7.4.1 Designing of Mechanical System for Sensor Chamber .....	78
7.4.2 Design of Boiler Automatic Blowdown Kit .....	80
7.4.3 Implematation of Mechanical Installation Blowdown Kit.....	80
7.5 Control Panel.....	83
7.6 Software Implementation .....	85
7.7 Ladder Program Function and Operation.....	87
CHAPTER 8 .....	91
TEST AND RESULTS DISCUSSION.....	91
8.1 Installation and Configurable Parameters of the System .....	91
8.2 Sensor Calibration.....	49
CHAPTER 9 .....	99
PROPOSED MAINTENANCE GUIDELINES .....	99
CHAPTER 10 .....	100
CONCLUSION AND FUTURE WORK .....	100
10.1 Conclusion .....	100
10.2 Future Work .....	101
REFERENCES.....	103
APPENDIXES .....	107