

References

- [1] D. P. Bentz and W. J. Weiss, *Internal curing: a 2010 state-of-the-art review*. US Department of Commerce, National Institute of Standards and Technology , 2011.
- [2] K. Kovler, “Smart additives for self-curing concrete,” *MRS Online Proceedings Library Archive*, vol. 1488, 2012.
- [3] ACI, “American concrete institute,” *ACI Concrete Terminology, Farmington Hills, MI*, vol. 1, pp. Pg;58–59, 2013.
- [4] R. Henkensiefken, D. Bentz, T. Nantung, and J. Weiss, “Volume change and cracking in internally cured mixtures made with saturated lightweight aggregate under sealed and unsealed conditions,” *Cement and Concrete Composites*, vol. 31, no. 7, pp. 427–437, 2009.
- [5] T. C. Powers, L. E. Copeland, and H. Mann, “Capillary continuity or discontinuity in cement pastes,” tech. rep., 1959.
- [6] A. Babcock and P. Taylor, “Impacts of internal curing on concrete properties: Literature review,” report, 2015.
- [7] A. M. Neville *et al.*, *Properties of concrete*, vol. 4. Longman London, 1995.
- [8] K. W. Meeks and N. J. Carino, *Curing of high-performance concrete: Report of the state-of-the-art*. Citeseer, 1999.
- [9] C. Rao and M. Darter, “Evaluation of internally cured concrete for paving applications,” *Applied Research Associates, Champaign, IL*, 2013.
- [10] K. Raoufi, J. Schlitter, D. Bentz, and J. Weiss, “Parametric assessment of stress development and cracking in internally cured restrained mortars experiencing autogenous deformations and thermal loading,” *Advances in Civil Engineering*, vol. 2011, 2011.

- [11] M. Golias, J. Castro, and J. Weiss, “The influence of the initial moisture content of lightweight aggregate on internal curing,” *Construction and Building Materials*, vol. 35, pp. 52–62, 2012.
- [12] S. Ahmad, “Reinforcement corrosion in concrete structures, its monitoring and service life predictiona review,” *Cement and Concrete Composites*, vol. 25, no. 4-5, pp. 459–471, 2003.
- [13] N. Delatte *et al.*, “Evaluation of high absorptive materials to improve internal curing of low permeability concrete:[executive summary],” tech. rep., Ohio. Dept. of Transportation. Office of Research and Development, 2007.
- [14] R. Henkensiefken, P. Briatka, D. Bentz, T. Nantung, and J. Weiss, “Plastic shrinkage cracking in internally cured mixtures made with pre-wetted lightweight aggregate,” *Concrete international*, vol. 32, no. 2, pp. 49–54, 2010.
- [15] M. R. Geiker, D. P. Bentz, and O. M. Jensen, “Mitigating autogenous shrinkage by internal curing,” *ACI Special Publications*, pp. 143–154, 2004.
- [16] B. Persson and G. Fagerlund, “3 rd international research seminar on self-desiccation and its importance in concrete technology,” 2002.
- [17] T. Friggle and D. Reeves, “Internal curing of concrete paving: laboratory and field experience,” *Special Publication*, vol. 256, pp. 71–80, 2008.
- [18] C. Ozyildirim, “Evaluation of ultra-high-performance fiber-reinforced concrete, final report vctir 12-r1,” *Virginia Center for Transportation Innovation and Research, Charlottesville, VA, USA*, 2011.
- [19] E. E. Holt, *Early age autogenous shrinkage of concrete*, vol. 446. Technical Research Centre of Finland Espoo, Finland, 2001.
- [20] E.-i. Tazawa, S. Miyazawa, and T. Kasai, “Chemical shrinkage and autogenous shrinkage of hydrating cement paste,” *Cement and concrete research*, vol. 25, no. 2, pp. 288–292, 1995.
- [21] T. Zhang, P. Gao, R. Luo, Y. Guo, J. Wei, and Q. Yu, “Measurement of chemical shrinkage of cement paste: Comparison study of astm c 1608 and an improved method,” *Construction and Building Materials*, vol. 48, pp. 662–669, 2013.
- [22] D. P. Bentz, P. Lura, and J. W. Roberts, “Mixture proportioning for internal curing,” *Concrete international*, vol. 27, no. 02, pp. 35–40, 2005.

- [23] D. P. Bentz and K. A. Snyder, "Protected paste volume in concrete: Extension to internal curing using saturated lightweight fine aggregate," *Cement and concrete research*, vol. 29, no. 11, pp. 1863–1867, 1999.
- [24] D. F. Albery R, *Physical Chemistry*. John Wiley & Sons, 1980.
- [25] T. Ayano and F. H. Wittmann, "Drying, moisture distribution, and shrinkage of cement-based materials," *Materials and Structures*, vol. 35, no. 3, pp. 134–140, 2002.
- [26] Z.-B. Zhang and J. Zhang, "Experimental study on relationship between shrinkage strain and environmental humidity of concrete.," *Jianzhu Cailiao Xuebao(Journal of Building Materials)*, vol. 9, no. 6, pp. 720–723, 2006.
- [27] B. Bissonnette, P. Pierre, and M. Pigeon, "Influence of key parameters on drying shrinkage of cementitious materials," *Cement and Concrete Research*, vol. 29, no. 10, pp. 1655–1662, 1999.
- [28] T. Y. Lo, W. C. Tang, and H. Z. Cui, "The effects of aggregate properties on lightweight concrete," *Building and Environment*, vol. 42, no. 8, pp. 3025–3029, 2007.
- [29] ASTM-C330/C330M, "Standard specification for lightweight aggregates for structural concrete," 2009.
- [30] ASTM-C1761/C1761M, "Standard specification for lightweight aggregate for internal curing of concrete," 2017.
- [31] ENV12620, "European standard for aggregates for concrete," p. 136, 2000.
- [32] UNI-8520/2, "Italian standard for concrete aggregates," p. 12, 1997.
- [33] J. L. Clarke, *Structural Lightweight Aggregate Concrete*. British Cement Association, 2006.
- [34] ASTM-C33, "Standard specification for concrete aggregates," 2002.
- [35] NortheastSoliteCorporation, "Internal curing specifications," 2017. "http://nesolite.com/internal-curing-specifications/", [Online; accessed 12-May-2019]".
- [36] W. J. Weiss and L. Montanari, "Guide specification for internally curing concrete," report, 2017.

- [37] *Report 41: internal curing of concrete-state-of-the-art report of RILEM Technical Committee 196-ICC*, vol. 41. RILEM publications, 2007.
- [38] P. Procho and T. Piotrowski, “Bound water content measurement in cement pastes by stoichiometric and gravimetric analyses,” *Journal of Building Chemistry*, vol. 1, no. 1, pp. 18–25, 2016.
- [39] I. Hager, “Behaviour of cement concrete at high temperature,” *Bulletin of the Polish Academy of Sciences: Technical Sciences*, vol. 61, no. 1, pp. 145–154, 2013.
- [40] J. Franjione and N. Vasishtha, “The art and science of microencapsulation,” *Technology Today*, vol. 2, pp. 1–6, 1995.
- [41] A. S. Hoffman, “Hydrogels for biomedical applications,” *Advanced drug delivery reviews*, vol. 64, pp. 18–23, 2012.
- [42] P. D. Drumheller and J. A. Hubbell, “Densely crosslinked polymer networks of poly (ethylene glycol) in trimethylolpropane triacrylate for cell-adhesion-resistant surfaces,” *Journal of biomedical materials research*, vol. 29, no. 2, pp. 207–215, 1995.
- [43] F. Buchholz and T. Graham, “Modern superabsorbent polymer technology,” *Tew York: Wiley-VCH*, 1998.
- [44] O. M. Jensen and P. F. Hansen, “Water-entrained cement-based materials: Ii. experimental observations,” *Cement and Concrete Research*, vol. 32, no. 6, pp. 973–978, 2002.
- [45] M. T. Hasholt, M. H. S. Jespersen, and O. M. Jensen, “Mechanical properties of concrete with sap part i: Development of compressive strength,” in *International RILEM conference on use of superabsorbent polymers and other new additives in concrete*, p. 10, RILEM Publications SARL, 2010.
- [46] B. E. Byard, A. K. Schindler, R. W. Barnes, and A. Rao, “Cracking tendency of bridge deck concrete,” *Transportation Research Record*, vol. 2164, no. 1, pp. 122–131, 2010.
- [47] J.-P. Wang, E. Gallo, B. Franois, F. Gabrieli, and P. Lambert, “Capillary force and rupture of funicular liquid bridges between three spherical bodies,” *Powder Technology*, vol. 305, pp. 89–98, 2017.

- [48] T. C. Hansen and H. Narud, "Strength of recycled concrete made from crushed concrete coarse aggregate," *Concrete International*, vol. 5, no. 01, pp. 79–83, 1983.
- [49] S. T. Yildirim, C. Meyer, and S. Herfellner, "Effects of internal curing on the strength, drying shrinkage and freeze–thaw resistance of concrete containing recycled concrete aggregates," *Construction and Building Materials*, vol. 91, pp. 288–296, 2015.
- [50] H. Kim and D. Bentz, "Internal curing with crushed returned concrete aggregates for high performance concrete," in *NRMCA Concrete Technology Forum: Focus on Sustainable Development*, pp. 20–22, Citeseer, 2008.
- [51] R. De Gennaro, P. Cappelletti, G. Cerri, M. De'Gennaro, M. Dondi, S. Graziano, and A. Langella, "Campanian ignimbrite as raw material for lightweight aggregates," *Applied clay science*, vol. 37, no. 1-2, pp. 115–126, 2007.
- [52] C. Cheeseman and G. Viridi, "Properties and microstructure of lightweight aggregate produced from sintered sewage sludge ash," *Resources, Conservation and Recycling*, vol. 45, no. 1, pp. 18–30, 2005.
- [53] A. L. Bush, D. P. Bryan, and D. R. Hack, "Lightweight aggregates," *Industrial Minerals and Rocks: Commodities, Markets, and Uses*, pp. 181–194, 2006.
- [54] J. L. Clarke, *Structural lightweight aggregate concrete*. CRC Press, 1993.
- [55] K. Kovler and O. Jensen, "Internal curing of concrete, state-of-the-art report of rilem technical committee 196-icc," *RILEM Report*, vol. 41, 2007.
- [56] S. Weber and H. W. Reinhardt, "A new generation of high performance concrete: concrete with autogenous curing," *Advanced cement based materials*, vol. 6, no. 2, pp. 59–68, 1997.
- [57] P. Lura, "Autogenous deformation and internal curing of concrete," 2003.
- [58] E. Fakhfakh, W. Hajjaji, M. Medhioub, F. Rocha, A. López-Galindo, M. Setti, F. Kooli, F. Zargouni, and F. Jamoussi, "Effects of sand addition on production of lightweight aggregates from tunisian smectite-rich clayey rocks," *Applied Clay Science*, vol. 35, no. 3-4, pp. 228–237, 2007.
- [59] S. Zhutovsky, K. Kovler, and A. Bentur, "Autogenous curing of high-strength concrete using pre-soaked pumice and perlite sand," in *Self-desiccation and*

its importance in concrete technology, Proceedings 3rd International Research Seminar, Lund, Sweden, pp. 161–173, 2002.

- [60] M. H. Zhang and O. E. Gjvovr, “Mechanical properties of high-strength lightweight concrete,” *Materials Journal*, vol. 88, no. 3, pp. 240–247, 1991.
- [61] S. Weber and H. Reinhardt, “Manipulating the water content and microstructure of high performance concrete using autogeneous curing,” in *Modern concrete materials: binders, additions and admixtures*, pp. 567–577, Thomas Telford Publishing, 1999.
- [62] S.-C. Huang, F.-C. Chang, S.-L. Lo, M.-Y. Lee, C.-F. Wang, and J.-D. Lin, “Production of lightweight aggregates from mining residues, heavy metal sludge, and incinerator fly ash,” *Journal of hazardous materials*, vol. 144, no. 1, pp. 52–58, 2007.
- [63] K. A. V. D. Vaickelionis, Giedrius, “Production of expanded clay pellets by using non-selfbloating clay, lakes sapropel and glycerol,” *Materials Science*, vol. 17, no. 3, pp. 314–321, 2011.
- [64] L. Pioro and I. Pioro, “Production of expanded-clay aggregate for lightweight concrete from non-selfbloating clays,” *Cement and concrete composites*, vol. 26, no. 6, pp. 639–643, 2004.
- [65] O. M. Jensen, *Report 41: internal curing of concrete-state-of-the-art report of RILEM Technical Committee 196-ICC*, vol. 41. RILEM publications, 2007.
- [66] A. S. El-Dieb, T. A. El-Maaddawy, and A. A. Mahmoud, “Water-soluble polymers as self-curing agents in cement mixes,” *Advances in cement research*, vol. 24, no. 5, pp. 291–299, 2012.
- [67] S. Evangeline, “Self curing concrete and its inherent properties,” *International Journal of Engineering Research and Applications*, vol. 4, no. 8, 2014.
- [68] C. Gallé, “Effect of drying on cement-based materials pore structure as identified by mercury intrusion porosimetry: a comparative study between oven-, vacuum-, and freeze-drying,” *Cement and Concrete Research*, vol. 31, no. 10, pp. 1467–1477, 2001.
- [69] S. Diamond, “Mercury porosimetry: an inappropriate method for the measurement of pore size distributions in cement-based materials,” *Cement and concrete research*, vol. 30, no. 10, pp. 1517–1525, 2000.

- [70] B. Li, J. Mao, J. Lv, and L. Zhou, "Effects of micropore structure on hydration degree and mechanical properties of concrete in later curing age," *European Journal of Environmental and Civil Engineering*, vol. 20, no. 5, pp. 544–559, 2015.
- [71] Y. Tsunazawa, T. Yokoyama, and N. Nishiyama, "An experimental study on the rate and mechanism of capillary rise in sandstone," *Progress in Earth and Planetary Science*, vol. 3, no. 1, p. 8, 2016.
- [72] L. A. Richards, "Capillary conduction of liquids through porous mediums," *physics*, vol. 1, no. 5, pp. 318–333, 1931.
- [73] D. M. Mattox, "Chapter 2-substrate (real) surfaces and surface modification," *Handbook of Physical Vapor Deposition (PVD) Processing*, vol. 2, 2010.
- [74] O. Akinshipe and G. Kornelius, "Chemical and thermodynamic processes in clay brick firing technologies and associated atmospheric emissions metrics-a review," *J Pollut Eff Cont*, vol. 5, no. 190, p. 2, 2017.
- [75] D. M. Moore and R. C. Reynolds, *X-ray Diffraction and the Identification and Analysis of Clay Minerals*, vol. 322. Oxford university press Oxford, 1989.
- [76] H. Murray, "Applied clay mineralogy. developments in clay science, vol. 2," 2007.
- [77] A. Bennour, S. Mahmoudi, E. Srasra, S. Boussen, and N. Htira, "Composition, firing behavior and ceramic properties of the sejnne clays (northwest tunisia)," *Applied Clay Science*, vol. 115, pp. 30–38, 2015.
- [78] S. K. T. Khafaji and E. A. Al-Majed, "Synthesis of light expanded clay aggregates from iraqi raw materials," 2016.
- [79] D. Morgan, "Thermal analysisincluding evolved gas analysisof clay raw materials," *Applied clay science*, vol. 8, no. 2-3, pp. 81–89, 1993.
- [80] D. Dos Santos, R. Toledo, R. Faria Jr, J. Carri, M. Da Silva, L. Auler, and H. Vargas, "Evolved gas analysis of clay materials," *Review of scientific instruments*, vol. 74, no. 1, pp. 663–666, 2003.
- [81] C. M. Riley, "Relation of chemical properties to the bloating of clays," *Journal of the American Ceramic Society*, vol. 34, no. 4, pp. 121–128, 1951.

- [82] C. Vieira, P. Da Silva, F. Da Silva, J. Capitaneo, and S. Monteiro, “Microstructural evaluation and properties of a ceramic body for extruded floor tiles,” *Revista Matéria*, vol. 10, no. 4, pp. 526–536, 2005.
- [83] I. tuba, T. Hlan, T. Kaljuvee, and L. Vozr, “Investigation of dynamic mechanical properties of estonian clay arumetsa during firing,” *Applied Clay Science*, vol. 153, pp. 23–28, 2018.
- [84] J. Pacini, “Bloating and black coring,” *Laguna Clay Co*, 1999.
- [85] K. MacKenzie and C. Cardile, “A 57 fe mössbauer study of black coring phenomena in clay-based ceramic materials,” *Journal of Materials Science*, vol. 25, no. 6, pp. 2937–2942, 1990.
- [86] L. Gredmaier, C. Banks, and R. Pearce, “Calcium and sulphur distribution in fired clay brick in the presence of a black reduction core using micro x-ray fluorescence mapping,” *Construction and Building Materials*, vol. 25, no. 12, pp. 4477–4486, 2011.
- [87] C. Rathossi and Y. Pontikes, “Effect of firing temperature and atmosphere on ceramics made of nw peloponnese clay sediments. part i: Reaction paths, crystalline phases, microstructure and colour,” *Journal of the European Ceramic Society*, vol. 30, no. 9, pp. 1841–1851, 2010.
- [88] B. Butterworth and D. Honeyborne, “Bricks and clays of the hastings beds,” *Transactions of the British Ceramic Society*, vol. 51, pp. 211–259, 1952.
- [89] F. Negre, A. Barba, J. Amoros, and A. Escardino, “Oxidation of black core during the firing of ceramic ware-2. process kinetics,” *British Ceramic Transactions*, pp. 5–11, 1992.
- [90] R. Toledo, D. Dos Santos, R. Faria Jr, J. Carrió, L. Auler, and H. Vargas, “Gas release during clay firing and evolution of ceramic properties,” *Applied Clay Science*, vol. 27, no. 3-4, pp. 151–157, 2004.
- [91] A. Barba, F. Negre, M. Ortis, and A. Escardino, “Oxidation of black core during the firing of ceramic ware-3. influence of the thickness of the piece and the composition of the black core,” *British Ceramic Transactions*, vol. 91, pp. 36–46, 1992.

- [92] A. A. Kadir and A. Mohajerani, "Effect of heating rate on gas emissions and properties of fired clay bricks and fired clay bricks incorporated with cigarette butts," *Applied Clay Science*, vol. 104, pp. 269–276, 2015.
- [93] R. Arnold and G. H. Duncombe Jr, "Clay sewerpipe manufacture1 vi. heatbalance determinations," *Journal of the American Ceramic Society*, vol. 12, no. 6, pp. 410–422, 1929.
- [94] E. Rowden, *The firing of Bricks*. Brick Development Association, 1964.
- [95] B. Cicel, I. Novák, and I. Horváth, "Mineralogy and crystallochemistry of clays," *SAV, Bratislava*, 1981.
- [96] J. Hlavác, "Technology of silicates," *SNTL, Praha*, 1981.
- [97] A. A. Kadir and A. Mohajerani, "Effect of heating rate on gas emissions and properties of fired clay bricks and fired clay bricks incorporated with cigarette butts," *Applied Clay Science*, vol. 104, pp. 269–276, 2015.
- [98] W. Lee, G. Souza, C. McConville, T. Tarvornpanich, and Y. Iqbal, "Mullite formation in clays and clay-derived vitreous ceramics," *Journal of the European Ceramic Society*, vol. 28, no. 2, pp. 465–471, 2008.
- [99] S. Karaman, S. Ersahin, and H. Gunal, "Firing temperature and firing time influence on mechanical and physical properties of clay bricks," 2006.
- [100] E. Tsega, A. Mosisa, and F. Fufa, "Effects of firing time and temperature on physical properties of fired clay bricks," *American Journal of Civil Engineering*, vol. 5, no. 1, pp. 21–26, 2017.
- [101] P. M. Velasco, M. P. M. Ortiz, M. A. M. Gir, D. M. Melia, and J. H. Rehbein, "Development of sustainable fired clay bricks by adding kindling from vine shoot: Study of thermal and mechanical properties," *Applied Clay Science*, vol. 107, pp. 156–164, 2015.
- [102] M. Dondi, M. Marsigli, and I. Venturi, "Microstructure and mechanical properties of clay bricks: comparison between fast firing and traditional firing," *British Ceramic Transactions*, vol. 98, no. 1, pp. 12–18, 1999.
- [103] L. Loricci and A. Brusa, "Porous and vitrified single-fired tiles," *Materials & Equipment/Whitewares: Ceramic Engineering and Science Proceedings*, pp. 183–184, 1991.

- [104] “Methods of test for masonry units-part 4: determination of real and bulk density and of total and open porosity for natural stone masonry units.,” *UNE-EN 7724*, 1999.
- [105] A. C1424-10, “standard test method for monotonic compressive strength of advanced ceramics at ambient temperature,” no. Code No: 81.060.30., 2012.
- [106] S. Ahmari and L. Zhang, “Production of eco-friendly bricks from copper mine tailings through geopolymerization,” *Construction and building materials*, vol. 29, pp. 323–331, 2012.
- [107] J. Boulingui, C. Nkoumbou, D. Njoya, F. Thomas, and J. Yvon, “Characterization of clays from mezafe and mengono (ne-libreville, gabon) for potential uses in fired products,” *Applied Clay Science*, vol. 115, pp. 132–144, 2015.
- [108] P. Pialy, C. Nkoumbou, F. Villiras, A. Razafitianamaharavo, O. Barres, M. Pelletier, G. Ollivier, I. Bihannic, D. Njopwouo, and J. Yvon, “Characterization for industrial applications of clays from lembo deposit, mount bana (cameroon),” *Clay Minerals*, vol. 43, no. 3, pp. 415–435, 2008.
- [109] S. Mahmoudi, A. Bennour, E. Srasra, and F. Zargouni, “Characterization, firing behavior and ceramic application of clays from the gabes region in south tunisia,” *Applied Clay Science*, vol. 135, pp. 215–225, 2017.
- [110] I. Waclawska, “Dehydration and dehydroxylation of smectites. i: Dehydration and dehydroxylation kinetics,” *Mineralogia polonica*, vol. 15, no. 1-2, pp. 91–107, 1984.
- [111] H. Fan, B. Song, and Q. Li, “Thermal behavior of goethite during transformation to hematite,” *Materials Chemistry and Physics*, vol. 98, no. 1, pp. 148–153, 2006.
- [112] G. Brown, *Crystal structures of clay minerals and their X-ray identification*, vol. 5. The Mineralogical Society of Great Britain and Ireland, 1982.
- [113] M. F. Serra, M. S. Conconi, G. Suarez, E. Agietti, and N. Rendtorff, “Firing transformations of an argentinean calcareous commercial clay,” *Cermica*, vol. 59, no. 350, pp. 254–261, 2013.
- [114] F. Pardo, M. Jordan, and M. Montero, “Ceramic behaviour of clays in central chile,” *Applied Clay Science*, vol. 157, pp. 158–164, 2018.

- [115] S. Mahmoudi, A. Bennour, A. Meguebli, E. Srasra, and F. Zargouni, "Characterization and traditional ceramic application of clays from the douiret region in south tunisia," *Applied Clay Science*, vol. 127, pp. 78–87, 2016.
- [116] H. Azzouz, R. Alouani, and S. Tlig, "Mineralogical characterization of ceramic tiles prepared by a mixture of cretaceous and mio-pliocene clays from tunisia: factory and laboratory products," *Journal of the Ceramic Society of Japan*, vol. 119, no. 1386, pp. 93–100, 2011.
- [117] K. Heide and M. Fldvari, "High temperature mass spectrometric gas-release studies of kaolinite $Al_2 [Si_2O_5 (OH)_4]$ decomposition," *Thermochimica Acta*, vol. 446, no. 1-2, pp. 106–112, 2006.
- [118] A. C1424-10, "Common burnt clay building bricks specifications," *Indian Standard*, vol. fifth revision, no. IS 1077: 1992, 1992.
- [119] J. Martín-Márquez, J. M. Rincón, and M. Romero, "Effect of firing temperature on sintering of porcelain stoneware tiles," *Ceramics International*, vol. 34, no. 8, pp. 1867–1873, 2008.