

REFERNECES

- [1] Colombo City Ring diagram, Planning Branch, CEB, Colombo City, 2008.
- [2] Feeder pillar details, Operation Unit, CEB, Colombo City, 2008.
- [3] Report on loss reduction activities in Colombo City, Energy management unit, CEB, Colombo City, 2008.
- [4] Primary substation load readings, Operation Unit, CEB, Colombo City, 2006,2008.
- [5] Power factor correction and harmonic filtering, Spain,Circutor, 2006.
- [6] "Over loads," in Shunt power capacitors of the self healing type for a.c . systems having a rated voltage upto and including 1000V, IEC 60831-part 1, pp. 39, 1996.
- [7] Avoiding AC Capacitor Failures in Large UPS Systems, American Power Conversion, Revision 0, pp. 10-11, 2003.
- [8] "Service condions," in Shunt power capacitors of the self healing type for a.c . systems having a rated voltage upto and including 1000V, IEC 60831-part 1, pp. 17-19, 1996.
- [9] Surya Santoso, Roger C. Dugan, Peter Nedwick, Modeling Ferroresonance Phenomena in an Underground Distribution System, The IPST Conference, pp.2, 2001, Available <http://www.ipst.org/TechPapers/2001/IPST01Paper034.pdf>
- [10] Zia Emin, Yu Kwong Tong, Ferroresonance Experience in UK: Simulations and Measurements, The IPST Conference, pp.1, 2001, Available <http://www.ipst.org/TechPapers/2001/IPST01Paper006.pdf>
- [11] "Symptoms of ferroresonance", Wiki: Ferroresonance (1/2), Available <http://wapedia.mobi/en/Ferroresonance#5>

