



**COIR PITH ACTIVATED CARBON  
FOR THE REMOVAL OF  
DYES, ORGANICS AND HEAVY METALS  
FROM AQUEOUS SOLUTIONS**

By  
D.W.DHANUSEKERA

This thesis was submitted to the  
Department of Chemical & Process Engineering  
of the University of Moratuwa  
in partial, fulfillment of the requirements  
for the degree of  
Master of Science

Department of Chemical & Process Engineering  
University of Moratuwa  
Sri Lanka

2008

92926



## Abstract

Adsorption of textile dyes, organics and heavy metals onto coir pith based adsorbents from aqueous solutions were studied. Raw coir pith and thermally activated coir pith at 700°C were used as adsorbents. Batch experiments showed that both adsorbents are capable of binding appreciable amounts of impurities from aqueous solutions. Thermally activated coir pith was superior to raw coir pith for dyes and phenol removal. Heavy metal adsorption capacities for both adsorbents were similar. Batch adsorption experiments were conducted in detail for dye removal to determine the factors affecting adsorption and kinetics of the process. Fixed bed column experiments were performed to study practical applicability and breakthrough curves were obtained. The maximum adsorption was observed at solution pH values between 5-9 for Methylene blue and Malachite green. Solution pH value of 2 showed maximum adsorption for Nylosan blue. The adsorbent to solution ratio and the dye concentration in the solution affect the degree of dye removal. The equilibrium data were satisfactorily fitted to Freundlich isotherm. The kinetic data fits to pseudo second order model and kinetic parameters were calculated. Column experiments showed 'S' shaped breakthrough curves and the results followed Bed Depth Service Time (BDST) model. Fixed bed adsorption capacities were lower compared to batch experiments.