

Referances

- (1) Comyn J-2002-polymer Permiability. Elsevier Applied Science Publishers London and New York
- (2) Mueller C.2000-Breathable Polymer Flm Poduced by Microlayer co-Extrusion Process.Journal of Applied Polymer Science,78:816-828.
- (3) Dyson R. W.-1987-Spesiality of polymer1:1-10
- (4)Goott fried w.Ehrenstein -2002-Plymer Materials 6:169-179
- (5)Richard g Griskey -1995- Popolymer Process Engineering 7:278-310
- (6)Brydson J.A -Flow Properties of Polymer melt 1:1-45
- (7)Nam.P.Suh and Nak Ho Sung 1977 - Science and Technology of polymer processing
- (8)Witold Brostow 2001 Performance of plastic 11:238-252
- (9).Mccrum N.G,. Buckiey C.P, Bucknall C.B. -Principle of Polymer Engineering 7;264-290
- (10)Arthur N.Wilkinson and Anthony J.Ryan-Polymer Process and Structure Development - 6:332-430
- (11) Ward I.M. - Sructure and Properties of Oriented Polymers 9:421-446
- (12) Bhatnagar M.S. -2004- A Text book of Polyers 3:79-89
- (13)Joel R.Fried 1995- Polymer Science and Technology -8:290-294
- (14) Van Krevelen D.W. 1976- Rheology of Polymeric System
- (15) Carrean,De Kee,Chhabra-1997- Rheology Of Polymeric System 2:18-32