

LB / 72355

10

Department of Civil Engineering  
UNIVERSITY OF MORATUWA  
SRI LANKA


MEng in Environmental Engineering and Management

**FEASIBILITY STUDY ON  
WASTE OIL DISPOSAL IN CEMENT KILNS  
FOR SRI LANKA**



ප්‍රථමකාලයේ  
මොරටුව විශ්ව විද්‍යාලය, ශ්‍රී ලංකාව  
මොරටුව.

By



A T Thiruchelvam

Under the supervision of

Dr Ajith P de Alwis  
Department of Chemical & Process Engineering  
University of Moratuwa

72355  
624 "00"  
625-4-14

August 2000

72355



"This thesis was submitted to the Department of Civil Engineering of the University of Moratuwa, Sri Lanka, as a partial fulfillment of the requirements of the degree of Master of Engineering in Environmental Engineering and Management".

"This thesis has not been previously presented in whole or part to any University or Institute for a higher degree".



Signature of the candidate: ... *[Handwritten Signature]* .....

Date: ... *30/08/2000* .....

## ACKNOWLEDGEMENT

Firstly I sincerely thank my supervisor, Dr Ajith P de Alwis of the Department of Chemical & Process Engineering of the University of Moratuwa for his kind guidance, encouragement and assistance given to me for this thesis.

Puttalam Cement Company Limited extended its fullest support and cooperation to my thesis. I gratefully thank the Management, Mr Horst Hofmann, Vice President (Technical) and late Mr Priyantha de Silva, Manager operations of Puttalam Cement. Late Mr Priyantha de Silva provided the necessary information and guidance to me whenever required. I also thank Mr Raju Goyal, Operations Advisor for his valuable advice and Mr S H D Dharmasena, Sift Burner and other staff of Puttalam Cement for their assistance. I thank the Management and staff of Puttalam Cement again for their kind hospitality during my visits by providing food and lodging.

I thank Dr (Mrs) D Hewage, Head and Mr Silva, Lab Technical staff of the Department of Chemistry of the University of Colombo for providing the facilities and assistance for the determination of heavy metals in waste oil. I also thank Mr S A S Perera, Head and Energy Engineering technical staff Mr Jeyaweera and Mr Saranelis of the Department of Chemical and Process Engineering of the University of Moratuwa for providing facilities and assistance for the laboratory tests I carried out.

I also thank the following organization and people for their kind support, information and assistance given to me for this thesis:

- Mr R Manoharan, Deputy Director and Mr Sunil de Silva, System Analyst of the Central Environmental Authority.
- Mrs G Rathnayake, Statistician of the Department of Motor Traffic.
- Mr J L Fernando, Chemist of the Railway Department (Ratmalana).
- Mr Piyasena, Manager of Ceylon Petroleum Corporation.
- Owners and the staff of the services stations I visited

I extend my gratitude to the Ministry of Forestry and Environment for providing me the scholarship for this course; and my Company, Environment & Management Lanka (Pvt) Ltd and Mr Lal Rodrigo, Director-Administration for assisting and encouraging me in perusing this course.

I take this opportunity to thank Prof. (Mrs) N Ratnayake, the course co-ordinator, other course lectures and staff of the Department of Civil Engineering of the University of Moratuwa for their support and guidance given to us during the course of study.

*Dedication to my wife*



University of Moratuwa, Sri Lanka  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)

## ABSTRACT

### 1. Main Objective

To study the feasibility of disposing the waste oil in the existing Puttalam Cement Kilns for Sri Lanka. To achieve this objective, the current situation in terms of technologies (manufacturing, fuel firing, process control, dust emission equipment and performance, etc.) of Puttalam Cement and the financial viability was evaluated.

### 2. Introduction

Disposing of waste oil in Cement Kilns will give three fold benefits: getting rid of waste oil, almost without any residue, complete energy recovery which contribute to the economy of a country and special disposal facilities are not needed as an existing facility is utilised

High flame temperatures and the nature of the product make cement kilns attractive for the destruction of a variety of hazardous organic materials. With proper management, kilns constitute a much less costly alternative to dedicated waste incinerators. Tests by USEPA and others have demonstrated that destruction of organic compounds including, PCBs and organochlorine and organophosphorus pesticides, equals or surpasses that achieved in hazardous waste incinerators that operate at lower temperatures. Many toxic metallic compounds can also be burned in cement kilns in quantities that are small enough not to adversely affect product quality or safety, since they are bonded to the clinker and become part of the product.

### 3. Waste Oil

It refers to lubricating oils, hydraulic, transmission & heat transfer fluids and insulants that have gone through their intended use cycle and must be either disposed of or treated and re-used. **In this thesis**, waste oil from automotive **transport sector** is only considered. Other transport (aviation and maritime) sector and spent industrial oils are **not** included here as waste oil since these oils are contaminated with unknown pollutants.

### 4. Waste Oil Generation and Properties in Sri Lanka


A pilot survey was carried out to estimate the waste oil generation and centrally collectable amount. According to the survey results, in 1999 around 24,000 – 27,000 ton waste oil was generated by automotive transport sector in Sri Lanka. However, the known collectable amount is 4,500 (about 18% of the generated amount) while the estimated amount is around 17,400 ton per year in 1999 as given in Table 23. With time, awareness, incentives, and enforcement of regulation, the estimated amount can be collected.

The laboratory test results show that our waste oil property is within the literature values in terms of physical property and the contaminants such as heavy metals. However, it is interesting to note that the ASTM distillation curve of the waste oil distillate resembles kerosene oil and the quantity distilled also only 63%. This shows that the best option in World of waste oil disposal by rerefining back to lube base may not be possible in Sri Lanka and therefore, the best option for our waste oil is using as alternate fuel which is well supported by the high calorific test results ( $> 44,000$  kJ/kg). However, with the limited number of tests it is difficult to come to a firm conclusion. This is only an indication.

### 5. Puttalam Cement

Cement is manufactured by grinding an artificial rock called "clinker" very finely (to a few microns) mixing with a small amount of gypsum (approximately 4%). Clinker is produced by heating limestone (77%) and some other ingredients (23%) to around  $1450^{\circ}\text{C}$  in a kiln. At Puttalam Cement Factory, there are two identical rotary kilns. The length of a kiln is 54 m. The burner of the kilns were change recently by Rotaflam kiln burner which has an additional jacket tube for a waste oil gun.

A complete actual material balance could not be done with the current on line measured and recorded data at Puttalam Cement. Therefore, some assumptions were made using the equipment specifications and international norms in doing the material balance. The average amount of raw materials used for one



ton of clinker production is 1.7 tons whereas theoretical value is 1.53. With the provision of dust emission from kiln exhaust and clinker cooler at the emission standards this value can be 1.56. Current loss of materials in terms of clinker is 3,355 kg per hour that is 11% of clinker. According to the present production and the proposed Sri Lankan emission standards, the allowable dust emission from kiln exhaust and clinker cooler is only 10.3 kg/hr which is merely 0.034% and therefore the actual loss of clinker is 10.966% that is 3,344.7 kg/hr and 28,095 ton per year from one kiln.

The cyclones used for the clinker cooling air dust recovery has been replaced by bag houses which was reviewed to see whether the capacity and the review shows that the selection is good. The expected emission will be only 30 mg/Nm<sup>3</sup> which is very much less than emission standards.

Complete overhauling ESPs was done to recover more dust and to reduce the emission from the kiln exhausts. These overhauled ESPs will be used for only two years and after two years these ESPs will be replaced by bag houses. Therefore, the environmental issues will be under control for the disposal of waste oil.

The average thermal energy consumption for one kg of clinker production is 3.65 - 4.02 MJ. However, literature value for dry process is 2.88 to 3.40 MJ/kg. That is the actual consumption is 19 - 26% higher than the literature value.

#### ***Factors to be considered for the disposal of waste oil:***

When waste oil is disposed, the values of the critical parameters should not be increased above the clinker quality standard as given in Table 25. When comparing our waste oil property and the clinker quality standard, the critical parameters for Puttalam Cement will be lead (Pb) and cadmium (Cd).

The present values of Pb and Cd in the clinker is not known and therefore it is assumed here that these values are zero. When the capture of heavy metals in the clinker can be taken (Table 9) as 99.7% and the Cd and Pb concentrations in waste oil are 4 and 3,200 mg/l, material balance show that 32% of furnace oil can be replaced by waste oil. I.e. about 16,000 tons of waste oil can be disposed at Puttalam Cement kilns (two) annually. However, Puttalam Cement has the plan to replace only 10% of furnace oil waste oil and this value will depend on the Pb and Cd content in the raw materials.

The emission level of the critical parameters should not also be increased above the emission standard. When comparing our waste oil property and the proposed Sri Lankan emission standard for cement kiln exhaust, the critical parameters for Puttalam Cement will be lead (Pb) and cadmium (Cd).

When the heavy metals capturing % and dust removal %; and the concentration of heavy metals in waste oil vary, the amount of maximum waste oil disposable varies as given in Figure 27 (graph).

## **6. Conclusion**

Waste oil can be disposed in Puttalam Cement Kilns with some improvements to the existing situation mainly the kiln exhaust dust removal that is the efficiency of ESPs. During this study, the ESPs were repaired and therefore current performance to be determined based on material balance as given in this report or dust emission measurements. The current efficiency of the ESPs could not be calculated because the dust concentration before ESP is not available. Dust concentration after ESPs is also not measured but from the material balance it is about 48,744 mg/Nm<sup>3</sup>. It can be assumed that the ESP was not working. Therefore, the required efficiency of the ESP to meet the standard will be 99.4%. The data used for the material balance was for one day of one kiln and therefore it may not represent the whole system. But it can be improved by using weekly, monthly and yearly data. Some trial runs should be carried out and the following records to be established for future planning:

- Characteristics of waste oil
- Heavy metal contents in raw materials and clinker
- Material balance for individual components
- Capturing ratio of heavy metal by clinker

# TABLE OF CONTENTS...

Abstract.....	i
List of Tables .....	iii
List of Figures .....	iv
List of Attachmentss .....	v
List of Notations .....	vi
List of Abbreviations .....	vii
<b>1. INTRODUCTION.....</b>	<b>1</b>
1.1 OBJECTIVES OF THE STUDY .....	1
1.2 SCOPE OF THE STUDY .....	1
1.3 OVERVIEW RELATED TO THE SCOPE OF STUDY.....	2
1.3.1 General.....	2
1.3.2 Hazardous Waste Management.....	2
1.3.3 Using Cement Kilns for Waste Recycling or Disposal.....	4
1.4 BACKGROUND INFORMATION RELATED TO THE SCOPE OF STUDY IN SRI LANKA .....	4
1.4.1 Environmental Laws and Regulations.....	4
1.4.2 Hazardous Waste and Waste Oil Management in Sri Lanka.....	5
1.4.3 Lubricants in Sri Lanka .....	6
1.4.4 Cement Factories in Sri Lanka.....	7
<b>2. LITERATURE REVIEW.....</b>	<b>9</b>
2.1 LUBRICATING OILS.....	9
2.2 WASTE OIL GENERATION AND PROPERTIES.....	12
2.3 ENVIRONMENTAL AND HEALTH HAZARDS OF WASTE OILS.....	15
2.4 WASTE OIL MANAGEMENT.....	17
2.4.1 Collection of waste oil.....	17
2.4.2 Recycling, reuse and recovery of waste oil .....	18
2.4.3 Incineration .....	21
2.4.4 Disposal in Cement Kilns.....	24
2.5 CEMENT TECHNOLOGY.....	27
2.5.1 Manufacturing Process.....	27
2.5.1.1 Process description .....	27
2.5.1.2 Cement Kilns .....	28
2.5.2 Environmental Issues in Cement Manufacturing.....	29
2.5.2.1 Particulates .....	31
2.5.2.2 Gaseous substances.....	31
2.5.2.3 Other Environmental Considerations in Cement Industry .....	31
2.6 ENVIRONMENTAL POLLUTION CONTROL TECHNOLOGIES USED IN CEMENT INDUSTRIES .....	32
2.6.1 Particulate/dust control devices .....	32
2.6.2 Gaseous emission control.....	32
2.6.3 Solid Waste Disposal.....	33
<b>3. MATERIALS AND METHODS.....</b>	<b>34</b>
3.1 LITERATURE SURVEY - INTERNATIONAL, LOCAL AND INTERNET.....	36
3.2 DISCUSSION WITH RELEVANT ORGANISATIONS AND PERSONNEL.....	36
3.3 DATA COLLECTION FROM RELEVANT ORGANIZATIONS AND PERSONNEL .....	36
3.4 VISITS TO SERVICE STATIONS AND GARAGES TO IDENTIFY THE QUANTITY AND METHOD OF DISPOSAL OF WASTE OIL.....	36
3.5 LABORATORY TESTS.....	36
3.6 PILOT SURVEY TO UNDERSTAND THE QUANTITY GENERATED AND THE METHOD OF DISPOSAL OF WASTE OIL.....	37
3.7 VISITS TO PUTTALAM CEMENT FACTORY .....	38

<b>4. RESULTS .....</b>	<b>39</b>
4.1 DATA COLLECTION FROM RELEVANT ORGANISATION AND PERSONNEL.....	39
4.1.1 <i>From Literature</i> .....	39
4.1.2 <i>From the Central Environmental Authority</i> .....	40
4.1.3 <i>From the Department of Motor Traffic</i> .....	40
4.1.4 <i>From Ceylon Railway Department</i> .....	41
4.1.5 <i>From Service Stations and garages</i> .....	41
4.2 LABORATORY TESTS.....	44
4.3 PILOT SURVEY TO UNDERSTAND THE QUANTITY GENERATED AND THE DESTINATION OF MOTOR ENGINE WASTE OIL.....	46
4.4 VISITS TO PUTTALAM CEMENT FACTORY - EXISTING SITUATION .....	47
4.4.1 Background of Puttalam Cement.....	47
4.4.2 Process Description.....	48
4.4.3 Details of Process Steps involved with the Disposal of Waste Oil.....	49
4.4.3.1 <i>Production</i> .....	49
4.4.3.2 <i>Kiln Operation</i> .....	49
4.4.3.3 <i>Pre-heater and Kiln Feeding</i> .....	50
4.4.3.4 <i>Clinker Cooler</i> .....	50
4.4.3.5 <i>Fuel firing system</i> .....	50
4.4.4 Atmospheric Emissions and Control Systems.....	52
4.4.5 Process Control.....	53
4.4.6 Material balance for Puttalam Cement.....	53
4.4.6.1 <i>Material Balance for Preheater</i> .....	57
4.4.6.2 <i>Material Balance for Kiln</i> .....	58
4.4.6.3 <i>Material Balance for Clinker Cooler</i> .....	58
4.4.6.4 <i>Dust emissions from Puttalam Cement</i> .....	60
4.4.7 Thermal Energy Consumption.....	60
4.4.8 On-going and Future Activities at Puttalam Cement.....	60
4.4.8.1 <i>Production</i> .....	60
4.4.8.2 <i>Alternative fuel projects</i> .....	61
<b>5. DISCUSSION OF RESULTS.....</b>	<b>62</b>
5.1 ESTIMATION OF WASTE OIL GENERATION IN SRI LANKA BASED ON THE RESULTS.....	62
5.1.1 From the sale amount of the virgin oil.....	62
5.1.2 From the Automobile use patterns.....	62
5.1.3 From the Information obtained from individual generators.....	64
5.2 ESTIMATION OF WASTE OIL COLLECTABLE IN SRI LANKA.....	64
5.3 WASTE OIL PROPERTIES.....	65
5.4 MATERIAL AND ENERGY CONSUMPTION AT PUTTALAM CEMENT .....	65
5.5 MAXIMUM AND MINIMUM QUANTITY OF WASTE OIL DISPOSABLE AT PUTTALAM CEMENT.....	65
5.5.1 Determination of Maximum quantity of waste oil disposable.....	65
5.5.1.1 <i>Based on Cement quality</i> .....	66
5.5.1.2 <i>Based on Emission standards</i> .....	67
5.5.2 Determination of Minimum quantity of waste oil disposable.....	71
5.5.3 Process Control (Kiln and other related operations).....	76
5.5.4 Atmospheric emissions and control system.....	76
<b>6. CONCLUSION AND RECOMMENDATIONS .....</b>	<b>77</b>
6.1 CONCLUSION .....	77
6.2 RECOMMENDATIONS.....	78
6.2.1 For Puttalam Cement.....	78
6.2.2 For Waste Oil Collection.....	80
<b>7. LIST OF REFERENCES.....</b>	<b>82</b>



## List of Tables...

Table 1: Additives used in Lubricants.....	10
Table 2: Physico-chemical properties for selected lubricating oil basestocks .....	11
Table 3: Amount of waste oil collected and regenerated country wise in Europe (Late 1980s).....	12
Table 4: Contaminants of Potential Concern in Waste Oils.....	14
Table 5: General parameters of waste oils .....	14
Table 6: Used-oil Fuel Specification of US EPA.....	21
Table 7: Examples of rate of DREs of organics in cement kilns.....	25
Table 8: Example of capture of Chlorine in cement kilns.....	26
Table 9: Example of capture of heavy metals in the clinker .....	26
Table 10: Portland cement clinker compounds .....	28
Table 11: Materials used for experimental studies on waste oil characteristics.....	35
Table 12: Test methods of the Experiments.....	37
Table 13: Estimated annual generation of hazardous waste in Sri Lanka .....	39
Table 14: Number of service stations and garages registered with CEA as of Sep 1999.....	40
Table 15: No. of Vehicles on use in Sri Lanka as at December 1998 .....	41
Table 16: Waste oil generation from Rail Transport.....	41
Table 17: Gathered data from service stations .....	42
Table 18: Laboratory Tests Results - Properties of Waste Oils .....	44
Table 19: Laboratory Tests Results - ASTM distillation (Sample - 100 ml of mixed waste oil ).....	45
Table 20: Summary of the Pilot Survey Results .....	46
Table 21: Raw Materials & Production (actual & budgeted) details of Puttalam Cement.....	49
Table 22: Detail of Kiln's Zones of Puttalam Cement.....	50
Table 23: Estimation of Waste oil Generation from Motor Vehicles.....	64
Table 24: Estimated waste oil generation values from two estimation techniques .....	65
Table 25: Standard values for pollutants in Clinker and Cement.....	67
Table 26: Emission standards for incinerator.....	68
Table 27: The replaceable percentage of waste oil at different scenarios when Pb is 3,200 mg/l in waste oil (it is assumed that Cd & Pb contents are zero in the raw materials).....	70
Table 28: Maximum concentrations of Cd & Pb in waste oil without affecting the quality of clinker for certain amount of waste oil disposal (it is assumed that Cd & Pb contents are zero in the raw materials) .....	70

## List of Figures...

Figure 1: Schematic Diagram of Hazardous Waste Management System .....	3
Figure 2: Main type of Caltex automotive lubricants in Sri Lanka .....	6
Figure 3: "Holderbank" Presence World-wide .....	7
Figure 4: Location of Cement Factories in Sri Lanka.....	8
Figure 5: Improper burning of waste oil .....	16
Figure 6: Schematic Diagram of Waste oil Management System .....	17
Figure 7: Acid-clay rerefining process flow diagram .....	18
Figure 8: Solvent treatment-distillation-finishing rerefining process flow diagram.....	19
Figure 9: Distillation-hydrofinishing rerefining process flow diagram .....	19
Figure 10: A Waste oil rerefining facility in Hong Kong .....	20
Figure 11: Rerefing processes used in the waste oil rerefing facility ies in Hong Kong.....	20
Figure 12: Schematic diagram of a proper incineration system .....	21
Figure 13: Schematic diagram of a hazardous waste incinerator .....	22
Figure 14: Thermal decomposition of organic molecules over a period of two seconds under oxidising conditions.....	23
Figure 15: Cement Manufacturing Processes.....	28
Figure 16: Input and output of Cement Manufacturing Industries (Dry Process).....	29
Figure 17: Schematic Process Flow Diagram for Cement Manufacturing (Dry Process) .....	30
Figure 18: Kiln Exhaust By-pass system .....	33
Figure 19: Service Station in Sri Lanka .....	43
Figure 20: ASTM Distillation Curve for Mixed Waste Oil .....	45
Figure 21: A side view of a part of Puttalam Cement Factory.....	47
Figure 22: Process Flow Diagram of Puttalam Cement Factory .....	48
Figure 23: Schematic Diagram of Preheating system of Puttalam Cement .....	50
Figure 24: Oil Firing System of Puttalam Cement.....	51
Figure 25: Figure of Rotarflame kiln burner .....	51
Figure 27: The Graph of replaceable percentage of waste oil at different scenarios when Pb is 3,200 mg/l in waste oil (it is assumed that Cd & Pb contents are zero in the raw materials) .....	71
Figure 28: Graph of Max. con. Of Cd & Pb in waste oil Vs certain amount of waste oil disposal without affecting clinker quality.....	72
Figure 29: Schematic Diagram for Waste oil storage system at Puttalam Cement.....	81

## List of Attachments...

- Appendix 1 : Pilot survey results
- Appendix 2 : Kiln process flow diagram of Puttalam Cement
- Appendix 3 : Puttalam Cement Kiln surface temperature profile
- Appendix 4 : Operation log-sheet of Kiln in Puttalam Cement
- Appendix 5 : A tender advertisement in a News Paper for getting paddy husk
- Appendix 6 : Copy of the ITI Report on Gross Calorific Value of Waste oil



University of Moratuwa, Sri Lanka  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)

## Notations...

$Al_2O_3$ -	Aluminum oxide
As	Arsenic
$CaCO_3$ -	Calcium carbonate
$CaO$ -	Calcium oxide
Cd	Cadmium
CDDS -	Chlorodubezo-podioxin
CDF -	Chlorinated dibenzofurans
Cl	Chlorine
CO -	Carbon monoxide
$CO_2$ -	Carbon dioxide
Cu	Copper
DRE -	Destruction and removal efficiency
ESP -	Electrostatic precipitator
$Fe_2O_3$ -	Ferric oxide
HCl -	Hydrochloric acid
Hg	Mercury
HF -	Hydrogen fluoride
HVI -	High viscosity index
kg	kilo gram
LVI -	Low viscosity index
MJ	Mega joules
NO -	Nitric oxide
$NO_x$ -	Oxides of nitrogen
$O_2$	Oxygen
PAC -	Polynuclear aromatic carbon
Pb	Lead
PCB -	Polychlorinated biphenyl
PM	Particulate matters
PNA -	Polynuclear aromatic carbon
POHC -	Principal organic constituents
$SiO_2$ -	Silicon oxide
$SO_2$ -	Sulfur dioxide
TNA -	Total acid number
Ti	Titanium
V	Vanadium
Zn	Zinc

## Abbreviations...

CEA -	Central Environmental Authority
DIY	Do-it-yourselfers
DMT -	Department of Motor Traffic
EIA	Environmental Impact Assessment
EPL -	Environmental Protection License
ITI	Industrial Technology Institute
NEA -	National Environmental Act
NIMBY -	Not In My Back Yard
Nm <sup>3</sup>	Cubic meter and Normal conditions of 0°C, 760 mmHg and zero moisture
Puttalam Cement -	Puttalam Cement Company Limited
UNEP -	United Nations Environmental Program
USEPA -	United States Environmental Protection Agency



University of Moratuwa, Sri Lanka  
Electronic Theses & Dissertations  
[www.lib.mrt.ac.lk](http://www.lib.mrt.ac.lk)